

NET IMPEDANCE ( Z )						
Frequency	0.5 MHz	1 MHz	5 MHz	10 MHz	25 MHz	
Nominal (REF)	50 $\Omega$	60 $\Omega$	42 $\Omega$	39 $\Omega$	35 $\Omega$	
Minimum	38 $\Omega$	45 $\Omega$	33 $\Omega$	29 $\Omega$	26 $\Omega$	

**PRELIMINARY  
PRINT**

FERRITE CORE DIMENSIONS (SPEC): mm [in]


A	32.00 [1.260]	+	0.60 [.024]
B	18.20 [.717]	+	0.40 [.016]
C	38.00 [1.496]	+	0.60 [.024]
D	8.00 [.315]	+	0.20 [.008]
E	4.00 [.157]	+	0.25 [.010]

WEIGHT/1000 33.30 kgs [73.40 Lbs]

NOTES: UNLESS OTHERWISE SPECIFIED

1. COSMETIC SPECIFICATION REFER TO WI-QA-038.
2. THE CONTACT SURFACE NEED TO BE POLISHED.

RoHS

DIMENSIONS ARE IN mm[INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
							
				PROJECT/PART NUMBER:	REV	PART TYPE:	DRAWN BY:
				35U1260-320	P3	CNZ CORE	QIU
P3	ADD Z SPEC	03/06/18	Jcai	DATE:	12/21/17	SCALE:	1 : 1
P2	CHANGE C	01/12/18	QIU	CAD #	35U1260-320-P3	TOOL #	U1260
P1	PRELIMINARY DRAFT	12/21/17	QIU	MATERIAL: Ferrite			
REV	DESCRIPTION	DATE	INT				

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Laird Performance Materials:](#)

[35U1260-320](#)