

# NCV4276C

## Voltage Regulator - Low-Drop

### 400 mA

The NCV4276C is a 400 mA output current integrated low dropout regulator family designed for use in harsh automotive environments. It includes wide operating temperature and input voltage ranges. The device is offered with 3.3 V, 5.0 V, and adjustable voltage versions available in 2% output voltage accuracy. It has a high peak input voltage tolerance and reverse input voltage protection. It also provides overcurrent protection, overtemperature protection and inhibit for control of the state of the output voltage. The NCV4276C family is available in DPAK and D<sup>2</sup>PAK surface mount packages. The output is stable over a wide output capacitance and ESR range. The NCV4276C has improved startup behavior during input voltage transients.

The NCV4276C is pin for pin compatible with NCV4276B.

#### Features


- 3.3 V, 5.0 V, and Adjustable Voltage Version (from 2.5 V to 20 V)  
±2% Output Voltage
- 400 mA Output Current
- 500 mV (max) Dropout Voltage (5.0 V Output)
- Inhibit Input
- Very Low Current Consumption
- Fault Protection
  - ◆ +45 V Peak Transient Voltage
  - ◆ -42 V Reverse Voltage
  - ◆ Short Circuit
  - ◆ Thermal Overload
- NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These are Pb-Free Devices




ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)


#### MARKING DIAGRAMS



DPAK  
5-PIN  
DT SUFFIX  
CASE 175AA



D<sup>2</sup>PAK  
5-PIN  
DS SUFFIX  
CASE 936A



\*Tab is connected to Pin 3 on all packages.

A = Assembly Location  
WL, L = Wafer Lot  
Y = Year  
WW = Work Week  
G = Pb-Free Device  
XX = 33 (3.3 V)  
= 50 (5.0 V)  
= AJ (Adj. Voltage)

#### ORDERING INFORMATION

See detailed ordering and shipping information in the ordering information section on page 14 of this data sheet.

# NCV4276C




Figure 1. NCV4276C Block Diagram




Figure 2. NCV4276C Adjustable Block Diagram

## PIN FUNCTION DESCRIPTION

| Pin No. | Symbol  | Description  |
|---------|---------|--|
| 1       | I       | Input; Battery Supply Input Voltage.   |
| 2       | INH     | Inhibit; Set low-to inhibit.   |
| 3       | GND     | Ground; Pin 3 internally connected to heatsink.  |
| 4       | NC / VA | Not connected for fixed voltage version / Voltage Adjust Input for adjustable voltage version; use an external voltage divider to set the output voltage |
| 5       | Q       | Output; Bypass with a capacitor to GND. See Figures 3 to 8 and Regulator Stability Considerations section.   |

# NCV4276C

## MAXIMUM RATINGS

| Rating                                 | Symbol                 | Min                                     | Max  | Unit |
|--|------------------------|---|------|------|
| Input Voltage                          | $V_I$                  | -42                                     | 45   | V    |
| Input Peak Transient Voltage           | $V_I$                  | -                                       | 45   | V    |
| Inhibit INH Voltage                    | $V_{INH}$              | -42                                     | 45   | V    |
| Voltage Adjust Input VA                | $V_{VA}$               | -0.3                                    | 10   | V    |
| Output Voltage                         | $V_Q$                  | -1.0                                    | 40   | V    |
| Ground Current                         | $I_q$                  | -                                       | 100  | mA   |
| Input Voltage Operating Range (Note 1) | $V_I$                  | $V_Q + 0.5 \text{ V}$ or 4.5 V (Note 2) | 40   | V    |
| ESD Susceptibility                     | (Human Body Model)     | -                                       | 4.0  | kV   |
|  | (Machine Model)        | -                                       | 250  | V    |
|  | (Charged Device Model) | -                                       | 1.25 | kV   |
| Junction Temperature                   | $T_J$                  | -40                                     | 150  | °C   |
| Storage Temperature                    | $T_{stg}$              | -50                                     | 150  | °C   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

- Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.
- Minimum  $V_I = 4.5 \text{ V}$  or  $(V_Q + 0.5 \text{ V})$ , whichever is higher.

## LEAD TEMPERATURE SOLDERING REFLOW (Note 3)

| Lead Temperature Soldering  | $T_{SLD}$ |   |     | °C |
|---|-----------|---|-----|----|
| Reflow (SMD styles only), Lead, 60–150 s above 183, 30 s max at peak      |           | - | 240 |    |
| Reflow (SMD styles only), Lead Free, 60–150 s above 217, 40 s max at peak |           | - | 265 |    |
| Wave Solder (through hole styles only), 12 sec max                        |           | - | 310 |    |

- Per IPC / JEDEC J-STD-020C.

## THERMAL CHARACTERISTICS

| Characteristic | Test Conditions (Typical Value) |  | Unit |
|----------------|---------------------------------|--|------|
|----------------|---------------------------------|--|------|

### DPAK 5-PIN PACKAGE

|   | Min Pad Board (Note 4) | 1" Pad Board (Note 5) |     |
|---|------------------------|-----------------------|-----|
| Junction-to-Tab ( $\psi_{JLx}$ , $\psi_{JLx}$ )         | 3.8                    | 4.3                   | C/W |
| Junction-to-Ambient ( $R_{\theta JA}$ , $\theta_{JA}$ ) | 75.1                   | 58.5                  | C/W |

### D<sup>2</sup>PAK 5-PIN PACKAGE

|   | 0.4 sq. in. Spreader Board (Note 6) | 1.2 sq. in. Spreader Board (Note 7) |     |
|---|-------------------------------------|-------------------------------------|-----|
| Junction-to-Tab ( $\psi_{JLx}$ , $\psi_{JLx}$ )         | 5.4                                 | 5.4                                 | C/W |
| Junction-to-Ambient ( $R_{\theta JA}$ , $\theta_{JA}$ ) | 54.2                                | 43.3                                | C/W |

- 1 oz. copper, 0.26 inch<sup>2</sup> (168 mm<sup>2</sup>) copper area, 0.062" thick FR4.
- 1 oz. copper, 1.14 inch<sup>2</sup> (736 mm<sup>2</sup>) copper area, 0.062" thick FR4.
- 1 oz. copper, 0.373 inch<sup>2</sup> (241 mm<sup>2</sup>) copper area, 0.062" thick FR4.
- 1 oz. copper, 1.222 inch<sup>2</sup> (788 mm<sup>2</sup>) copper area, 0.062" thick FR4.

# NCV4276C

## ELECTRICAL CHARACTERISTICS ( $V_I = 13.5\text{ V}$ ; $-40^\circ\text{C} < T_J < 150^\circ\text{C}$ ; unless otherwise noted.)

| Characteristic                                      | Symbol                   | Test Conditions  | Min   | Typ | Max   | Unit          |
|---|--------------------------|--|-------|-----|-------|---------------|
| <b>OUTPUT</b>                                       |                          |  |       |     |       |               |
| Output Voltage, 5.0 V Version                       | $V_Q$                    | $5.0\text{ mA} < I_Q < 400\text{ mA}$ ,<br>$6.0\text{ V} < V_I < 28\text{ V}$                  | 4.9   | 5.0 | 5.1   | V             |
| Output Voltage, 5.0 V Version                       | $V_Q$                    | $5.0\text{ mA} < I_Q < 200\text{ mA}$ ,<br>$6.0\text{ V} < V_I < 40\text{ V}$                  | 4.9   | 5.0 | 5.1   | V             |
| Output Voltage, 3.3 V Version                       | $V_Q$                    | $5.0\text{ mA} < I_Q < 400\text{ mA}$ ,<br>$4.5\text{ V} < V_I < 28\text{ V}$                  | 3.234 | 3.3 | 3.366 | V             |
| Output Voltage, 3.3 V Version                       | $V_Q$                    | $5.0\text{ mA} < I_Q < 200\text{ mA}$ ,<br>$4.5\text{ V} < V_I < 40\text{ V}$                  | 3.234 | 3.3 | 3.366 | V             |
| Output Voltage, Adjustable Version                  | $AV_Q$                   | $5.0\text{ mA} < I_Q < 400\text{ mA}$<br>$V_{Q+1} < V_I < 40\text{ V}$<br>$V_I > 4.5\text{ V}$ | -2%   | -   | +2%   | V             |
| Output Current Limitation                           | $I_Q$                    | $V_Q = 90\% V_{Q\text{TYP}}$<br>( $V_{Q\text{TYP}} = 2.5\text{ V}$ for ADJ version)            | 400   | 600 | 1100  | mA            |
| Quiescent Current (Sleep Mode)<br>$I_q = I_I - I_Q$ | $I_q$                    | $V_{\text{INH}} = 0\text{ V}$  | -     | -   | 10    | $\mu\text{A}$ |
| Quiescent Current, $I_q = I_I - I_Q$                | $I_q$                    | $I_Q = 1.0\text{ mA}$  | -     | 95  | 200   | $\mu\text{A}$ |
| Quiescent Current, $I_q = I_I - I_Q$                | $I_q$                    | $I_Q = 250\text{ mA}$  | -     | 5   | 15    | mA            |
| Quiescent Current, $I_q = I_I - I_Q$                | $I_q$                    | $I_Q = 400\text{ mA}$  | -     | 10  | 35    | mA            |
| Dropout Voltage,<br>Adjustable Version              | $V_{\text{DR}}$          | $I_Q = 250\text{ mA}$ ,<br>$V_{\text{DR}} = V_I - V_Q$<br>$V_I > 4.5\text{ V}$                 | -     | 250 | 500   | mV            |
| Dropout Voltage (5.0 V Version)                     | $V_{\text{DR}}$          | $I_Q = 250\text{ mA}$ (Note 8)   | -     | 250 | 500   | mV            |
| Load Regulation                                     | $\Delta V_{\text{Q,LO}}$ | $I_Q = 5.0\text{ mA}$ to $400\text{ mA}$   | -     | 3.0 | 20    | mV            |
| Line Regulation                                     | $\Delta V_Q$             | $\Delta V_I = 12\text{ V}$ to $32\text{ V}$ ,<br>$I_Q = 5.0\text{ mA}$                         | -     | 4.0 | 15    | mV            |
| Power Supply Ripple Rejection                       | PSRR                     | $f_r = 100\text{ Hz}$ , $V_r = 0.5\text{ V}_{\text{PP}}$                                       | -     | 70  | -     | dB            |

## INHIBIT

|                                   |                  |                                 |     |     |     |               |
|-----------------------------------|------------------|---------------------------------|-----|-----|-----|---------------|
| Inhibit Voltage, Output High      | $V_{\text{INH}}$ | $V_Q \geq V_{\text{QMIN}}$      | -   | 2.3 | 2.8 | V             |
| Inhibit Voltage, Output Low (Off) | $V_{\text{INH}}$ | $V_Q \leq 0.1\text{ V}$         | 1.8 | 2.2 | -   | V             |
| Input Current                     | $I_{\text{INH}}$ | $V_{\text{INH}} = 5.0\text{ V}$ | 5.0 | 10  | 20  | $\mu\text{A}$ |

## THERMAL SHUTDOWN


|                                       |                 |                       |     |   |     |                  |
|---------------------------------------|-----------------|-----------------------|-----|---|-----|------------------|
| Thermal Shutdown Temperature (Note 9) | $T_{\text{SD}}$ | $I_Q = 5.0\text{ mA}$ | 150 | - | 210 | $^\circ\text{C}$ |
|---------------------------------------|-----------------|-----------------------|-----|---|-----|------------------|

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


8. Measured when the output voltage  $V_Q$  has dropped 100 mV from the nominal valued obtained at  $V = 13.5\text{ V}$ .

9. Guaranteed by design, not tested in production.

## NCV4276C



**Figure 3. Applications Circuit; Fixed Voltage Version**



$C_b^*$  - Required if usage of low ESR output capacitor  $C_Q$  is demand, see Regulator Stability Considerations section

**Figure 4. Applications Circuit; Adjustable Voltage Version**

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 5. Output Stability with Output Capacitor ESR, Fixed Versions (5.0 V and 3.3 V)




Figure 6. Output Stability with Output Capacitor ESR, Fixed Versions (5.0 V and 3.3 V)




Figure 7. Output Stability with Output Capacitor ESR, Adjustable Version






Figure 8. Output Stability with Output Capacitor ESR, Adjustable Version


TYPICAL PERFORMANCE CHARACTERISTICS – Fixed Versions




**Figure 9. Output Voltage vs. Junction Temperature, 5.0 V Version**




**Figure 10. Output Voltage vs. Junction Temperature, 3.3 V Version**




**Figure 11. Quiescent Current vs. Input Voltage, 5.0 V Version**



**Figure 12. Quiescent Current vs. Input Voltage, 3.3 V Version**



**Figure 13. Output Voltage vs. Input Voltage, 5.0 V Version**



**Figure 14. Output Voltage vs. Input Voltage, 3.3 V Version**

TYPICAL PERFORMANCE CHARACTERISTICS – Fixed Versions




Figure 15. Input Current vs. Input Voltage, 5.0 V Version




Figure 16. Input Current vs. Input Voltage, 3.3 V Version




Figure 17. Dropout Voltage vs. Output Current, Only 5 V Version




Figure 18. Maximum Output Current vs. Input Voltage




Figure 19. Quiescent Current vs. Output Current (High Load)




Figure 20. Quiescent Current vs. Output Current (Low Load)

TYPICAL PERFORMANCE CHARACTERISTICS – Adjustable Version




Figure 21. Output Voltage vs. Junction Temperature




Figure 22. Quiescent Current vs. Input Voltage




Figure 23. Output Voltage vs. Input Voltage




Figure 24. Input Current vs. Input Voltage

TYPICAL PERFORMANCE CHARACTERISTICS – Adjustable Version




Figure 25. Dropout Voltage vs. Output Current, Output Voltage set to 5.0 V




Figure 26. Maximum Output Current vs. Input Voltage




Figure 27. Quiescent Current vs. Output Current (High Load)




Figure 28. Quiescent Current vs. Output Current (Low Load)

### Circuit Description

The NCV4276C is an integrated low dropout regulator that provides a regulated voltage at 400 mA to the output. It is enabled with an input to the inhibit pin. The regulator voltage is provided by a PNP pass transistor controlled by an error amplifier with a bandgap reference, which gives it the lowest possible dropout voltage. The output current capability is 400 mA, and the base drive quiescent current is controlled to prevent oversaturation when the input voltage is low or when the output is overloaded. The regulator is protected by both current limit and thermal shutdown. Thermal shutdown occurs above 150°C to protect the IC during overloads and extreme ambient temperatures.

### Regulator

The error amplifier compares the reference voltage to a sample of the output voltage ( $V_O$ ) and drives the base of a PNP series pass transistor via a buffer. The reference is a bandgap design to give it a temperature-stable output. Saturation control of the PNP is a function of the load current and input voltage. Oversaturation of the output power device is prevented, and quiescent current in the ground pin is minimized. See Figure 4, Test Circuit, for circuit element nomenclature illustration.

### Regulator Stability Considerations

The input capacitors ( $C_{I1}$  and  $C_{I2}$ ) are necessary to stabilize the input impedance to avoid voltage line influences. Using a resistor of approximately 1.0  $\Omega$  in series with  $C_{I2}$  can stop potential oscillations caused by stray inductance and capacitance.

The output capacitor helps determine three main characteristics of a linear regulator: startup delay, load transient response and loop stability. The capacitor value and type should be based on cost, availability, size and temperature constraints. The aluminum electrolytic capacitor is the least expensive solution, but, if the circuit operates at low temperatures ( $-25^\circ\text{C}$  to  $-40^\circ\text{C}$ ), both the value and ESR of the capacitor will vary considerably. The capacitor manufacturer's data sheet usually provides this information.

The value for the output capacitor  $C_O$ , shown in Figure 3, should work for most applications; see also Figures 5 to 8 for output stability at various load and Output Capacitor ESR conditions. Stable region of ESR in Figures 5 to 8 shows ESR values at which the LDO output voltage does not have any permanent oscillations at any dynamic changes of output load current. Marginal ESR is the value at which the output voltage waving is fully damped during four periods after the load change and no oscillation is further observable.

ESR characteristics were measured with ceramic capacitors and additional series resistors to emulate ESR. Low duty cycle pulse load current technique has been used to maintain junction temperature close to ambient temperature.

Minimum ESR for  $C_O = 10 \mu\text{F}$  and  $22 \mu\text{F}$  is native ESR of ceramic capacitor with which the fixed output voltage devices are performing stable. Murata ceramic capacitors were used,

GCM32ER71E106KA57 (10  $\mu\text{F}$ , 25V, X7R, 1210),

GRM32ER71E226ME15 (22  $\mu\text{F}$ , 25V, X7R, 1210).

### Calculating Bypass Capacitor

If usage of low ESR ceramic capacitors is demand in case of Adjustable Regulator, connect the bypass capacitor  $C_b$  between Voltage Adjust pin and Q pin according to Applications circuit at Figure 4.

Parallel combination of bypass capacitor  $C_b$  with the feedback resistor  $R_1$  contributes in the device transfer function as an additional zero and affects the device loop stability, therefore its value must be optimized. Attention to the Output Capacitor value and its ESR must be paid. See also Stability in High Speed Linear LDO Regulators Application Note, AND8037/D for more information.

Optimal value of bypass capacitor is given by following expression

$$C_b = \frac{1}{2 \times \pi \times f_z \times R_1} \cdot (F)$$

where

$R_1$  = the upper feedback resistor

$f_z$  = the frequency of the zero added into the device transfer function by  $R_1$  and  $C_b$  external components.

Set the  $R_1$  resistor according to output voltage requirement. Chose the  $f_z$  with regard on the output capacitance  $C_O$ , refer to the table below.

| $C_O$ ( $\mu\text{F}$ ) | 10      | 22      | 47     |
|-------------------------|---------|---------|--------|
| $f_z$ Range (kHz)       | 16 – 18 | 11 – 18 | 8 – 18 |

Ceramic capacitors and its part numbers listed bellow have been used as low ESR output capacitors  $C_O$  from the table above to define the frequency ranges of additional zero required for stability.

GCM32ER71E106KA57 (10  $\mu\text{F}$ , 25V, X7R, 1210)

GRM32ER71E226ME15 (22  $\mu\text{F}$ , 25V, X7R, 1210)

GRM32ER61C476ME15 (47  $\mu\text{F}$ , 16 V, X5R, 1210)

### Inhibit Input

The inhibit pin is used to turn the regulator on or off. By holding the pin down to a voltage less than 1.8 V, the output of the regulator will be turned off. When the voltage on the Inhibit pin is greater than 2.8 V, the output of the regulator will be enabled to power its output to the regulated output voltage. The inhibit pin may be connected directly to the input pin to give constant enable to the output regulator.

### Setting the Output Voltage (Adjustable Version)

The output voltage range of the adjustable version can be set between 2.5 V and 20 V. This is accomplished with an external resistor divider feeding back the voltage to the IC back to the error amplifier by the voltage adjust pin VA.

The internal reference voltage is set to a temperature stable reference of 2.5 V.

The output voltage is calculated from the following formula. Ignoring the bias current into the VA pin:

$$V_Q = [(R1 + R2) * V_{ref}] / R2$$

Use  $R2 < 50\text{ k}$  to avoid significant voltage output errors due to VA bias current.

Connecting VA directly to Q without R1 and R2 creates an output voltage of 2.5 V.

Designers should consider the tolerance of R1 and R2 during the design phase.

The input voltage range for operation (pin 1) of the adjustable version is between  $(V_Q + 0.5\text{ V})$  and 40 V. Internal bias requirements dictate a minimum input voltage of 4.5 V. The dropout voltage for output voltages less than 4.0 V is  $(4.5\text{ V} - V_Q)$ .

### Calculating Power Dissipation in a Single Output Linear Regulator

The maximum power dissipation for a single output regulator (Figure 29) is:

$$P_{D(max)} = [V_{I(max)} - V_{Q(min)}] I_{Q(max)} + V_{I(max)} I_q \quad (1)$$

where

- $V_{I(max)}$  is the maximum input voltage,
- $V_{Q(min)}$  is the minimum output voltage,
- $I_{Q(max)}$  is the maximum output current for the application,
- $I_q$  is the quiescent current the regulator consumes at  $I_{Q(max)}$ .

Once the value of  $P_{D(max)}$  is known, the maximum permissible value of  $R_{\theta JA}$  can be calculated:

$$R_{\theta JA} = \frac{150^{\circ}\text{C} - T_A}{P_D} \quad (2)$$

The value of  $R_{\theta JA}$  can then be compared with those in the package section of the data sheet. Those packages with  $R_{\theta JA}$  less than the calculated value in Equation 2 will keep the die temperature below 150°C.

In some cases, none of the packages will be sufficient to dissipate the heat generated by the IC, and an external heatsink will be required.




Figure 29. Single Output Regulator with Key Performance Parameters Labeled

### Heatsinks

A heatsink effectively increases the surface area of the package to improve the flow of heat away from the IC and into the surrounding air.

Each material in the heat flow path between the IC and the outside environment will have a thermal resistance. Like series electrical resistances, these resistances are summed to determine the value of  $R_{\theta JA}$ :

$$R_{\theta JA} = R_{\theta JC} + R_{\theta CS} + R_{\theta SA} \quad (3)$$


where

- $R_{\theta JC}$  is the junction-to-case thermal resistance,
- $R_{\theta CS}$  is the case-to-heatsink thermal resistance,
- $R_{\theta SA}$  is the heatsink-to-ambient thermal resistance.


$R_{\theta JC}$  appears in the package section of the data sheet. Like  $R_{\theta JA}$ , it too is a function of package type.  $R_{\theta CS}$  and  $R_{\theta SA}$  are functions of the package type, heatsink and the interface between them. These values appear in data sheets of heatsink manufacturers.

Thermal, mounting, and heatsinking considerations are discussed in the ON Semiconductor application note AN1040/D.


# NCV4276C




**Figure 30.  $R_{\theta JA}$  vs. Copper Spreader Area, DPAK 5-Lead**



**Figure 31.  $R_{\theta JA}$  vs. Copper Spreader Area, D<sup>2</sup>PAK 5-Lead**



**Figure 32. Single-Pulse Heating Curves, DPAK 5-Lead**



**Figure 33. Single-Pulse Heating Curves, D<sup>2</sup>PAK 5-Lead**

# NCV4276C




Figure 34. Duty Cycle for 1" Spreader Boards, DPAK 5-Lead




Figure 35. Duty Cycle for 1" Spreader Boards, D<sup>2</sup>PAK 5-Lead

## ORDERING INFORMATION

| Device           | Output Voltage Accuracy | Output Voltage | Package                             | Shipping <sup>†</sup>               |                    |
|------------------|-------------------------|----------------|-------------------------------------|-------------------------------------|--------------------|
| NCV4276CDT33RKG  | 2%                      | 3.3 V          | DPAK, 5-Pin (Pb-Free)               | 2500 / Tape & Reel                  |                    |
| NCV4276CDS33R4G  |                         |                | D <sup>2</sup> PAK, 5-Pin (Pb-Free) | 800 / Tape & Reel                   |                    |
| NCV4276CDT50RKG  |                         | 5.0 V          | DPAK, 5-Pin (Pb-Free)               | 2500 / Tape & Reel                  |                    |
| NCV4276CDS50R4G  |                         |                | D <sup>2</sup> PAK, 5-Pin (Pb-Free) | 800 / Tape & Reel                   |                    |
| NCV4276CDTADJRKG |                         | Adjustable     | Adjustable                          | DPAK, 5-Pin (Pb-Free)               | 2500 / Tape & Reel |
| NCV4276CDTADJT5G |                         |                |                                     | DPAK, 5-Pin (Pb-Free)               | 2500 / Tape & Reel |
| NCV4276CDSADJR4G |                         |                |                                     | D <sup>2</sup> PAK, 5-Pin (Pb-Free) | 800 / Tape & Reel  |


<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.



DPAK-5, CENTER LEAD CROP  
CASE 175AA  
ISSUE B

DATE 15 MAY 2014


SCALE 1:1




- NOTES:  
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.  
2. CONTROLLING DIMENSION: INCH.

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.235     | 0.245 | 5.97        | 6.22 |
| B   | 0.250     | 0.265 | 6.35        | 6.73 |
| C   | 0.086     | 0.094 | 2.19        | 2.38 |
| D   | 0.020     | 0.028 | 0.51        | 0.71 |
| E   | 0.018     | 0.023 | 0.46        | 0.58 |
| F   | 0.024     | 0.032 | 0.61        | 0.81 |
| G   | 0.180 BSC |       | 4.56 BSC    |      |
| H   | 0.034     | 0.040 | 0.87        | 1.01 |
| J   | 0.018     | 0.023 | 0.46        | 0.58 |
| K   | 0.102     | 0.114 | 2.60        | 2.89 |
| L   | 0.045 BSC |       | 1.14 BSC    |      |
| R   | 0.170     | 0.190 | 4.32        | 4.83 |
| R1  | 0.185     | 0.210 | 4.70        | 5.33 |
| S   | 0.025     | 0.040 | 0.63        | 1.01 |
| U   | 0.020     | ---   | 0.51        | ---  |
| V   | 0.035     | 0.050 | 0.89        | 1.27 |
| Z   | 0.155     | 0.170 | 3.93        | 4.32 |

RECOMMENDED  
SOLDERING FOOTPRINT\*



GENERIC  
MARKING DIAGRAMS\*




- IC**
- XXXXXXG  
ALYWW
- Discrete**
- AYWW  
XXX  
XXXXXXG
- XXXXXX = Device Code
  - A = Assembly Location
  - L = Wafer Lot
  - Y = Year
  - WW = Work Week
  - G = Pb-Free Package

\*For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, [SOLDERRM/D](#).

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present.

|                         |                                |  |
|-------------------------|--------------------------------|--|
| <b>DOCUMENT NUMBER:</b> | <b>98AON12855D</b>             | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>DPAK-5 CENTER LEAD CROP</b> | <b>PAGE 1 OF 1</b>   |







onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.



D<sup>2</sup>PAK 5-LEAD  
CASE 936A-02  
ISSUE E

DATE 28 JUL 2021

SCALE 1:1




NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION INCHES
3. TAB CONTOUR OPTIONAL WITHIN DIMENSIONS A AND K.
4. DIMENSIONS U AND V ESTABLISH A MINIMUM MOUNTING SURFACE FOR TERMINAL 4.
5. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH OR GATE PROTRUSIONS. MOLD FLASH AND GATE PROTRUSIONS NOT TO EXCEED 0.025 (0.635) MAXIMUM.

| DIM | INCHES |       | MILLIMETERS |        |
|-----|--------|-------|-------------|--------|
|     | MIN.   | MAX.  | MIN.        | MAX.   |
| A   | 0.396  | 0.403 | 9.804       | 10.236 |
| B   | 0.356  | 0.368 | 9.042       | 9.347  |
| C   | 0.170  | 0.180 | 4.318       | 4.572  |
| D   | 0.026  | 0.036 | 0.660       | 0.914  |
| Ed  | 0.045  | 0.055 | 1.143       | 1.397  |
| Es  | 0.018  | 0.026 | 0.457       | 0.660  |
| G   | 0.067  | BSC   | 1.702       | BSC    |
| H   | 0.539  | 0.579 | 13.691      | 14.707 |
| K   | 0.050  | REF   | 1.270       | REF    |
| L   | 0.000  | 0.010 | 0.000       | 0.254  |
| M   | 0.088  | 0.102 | 2.235       | 2.591  |
| N   | 0.018  | 0.026 | 0.457       | 0.660  |
| P   | 0.058  | 0.078 | 1.473       | 1.981  |
| R   | 0°     | 8°    | 0°          | 8°     |
| S   | 0.116  | REF   | 2.946       | REF    |
| U   | 0.200  | MIN   | 5.080       | MIN    |
| V   | 0.250  | MIN   | 6.350       | MIN    |

GENERIC  
MARKING DIAGRAM\*



- xxxxxx = Device Code
- A = Assembly Location
- WL = Wafer Lot
- Y = Year
- WW = Work Week
- G = Pb-Free Package



\* For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "μ", may or may not be present. Some products may not follow the Generic Marking.

|                  |              |  |
|------------------|--------------|--|
| DOCUMENT NUMBER: | 98ASH01006A  | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | D2PAK 5-LEAD | PAGE 1 OF 1  |

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)