2. MATERIAL: CARBON FILLED POLY-PROPYLENE. STATIC DECAY MEETS MIL-PRF-81705D. SURFACE RESISTIVITY PER ASTM D 257-99 (2005): <1.0 X 10<sup>12</sup> OHMS/SQUARE. COLOR: BLACK.

MATERIAL: SEE NOTES Temper: Per Spec.: R/M P/N ref: Certification required: N/A	UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE: Decimals: .XX ± 0.01 Concentricity: Decimals: .XXX ± 0.010 Angles: ± 5° Decimals: .XXXX ± 0.0100 Radius: ± Parts are to be symmetrical about centerline within ± .004 Surfaces to be flat, perpendicular parallel within .004 T.I.R. Dimensions are in inches/DO NOT SCALE PRINT Surface finish to be or better  APPLIC ATION: verSI SERIES			AirBorn Georgetown, Texas 78626			Cage Code 10400	
HEAT TREAT: N/A Per Spec.: Certification required: N/A						Released authorized for production DUST COVER,	MALE	
FINISH: N/A Per Spec.: Certification required: N/A	A	SEE ECO	TAD W65136 072121 DL 072121	021320 CK.	T T	verSI SER	IES	SIZE
	REV	DESC RIPTION	DR. BY ECO NO. DATE APPD. BY	RLS 021320	L E	ESD		
MAKE FROM: N/A NEXT ASSY: N/A		CHARAC TERISTIC THIRD ANGLE CHARAC TERISTIC PROJEC TION	REL. RAS 052820	APPD. JC T 021320	DWG #	₩ VDCM−X	X-XX REV. A	SHEET 1/1

Α

С