




All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

ISO 20860-1, DIN 72594-1

Material

Housing

PBT-GF20

Secondary Lock

PBT-GF10

Mechanical data

Mating cycles	≥ 25
Retention force latch	≥ 110 N
Retention force primary lock	≥ 80 N
Retention force secondary lock	≥ 60 N
Coding efficiency	≥ 40 N

Technical Data Sheet

Rosenberger

FAKRA - HF

PLASTIC HOUSING

59Z113-000-Y

Environmental data

Temperature range	-40°C to +105°C
Thermal shock	DIN 72594-2 clause 8.2
Temperature and humidity	DIN 72594-2 clause 8.3
Vibration and mechanical shock	DIN 72594-2 clause 8.1
Dry heat	DIN 72594-2 clause 8.4
RoHS	compliant

Application

Applicable e.g. for following connectors: 59K13O-1xx^{*)}, 59K13D-1xx^{*)}, 59K13F-1xx^{*)}, 59K16A-1xx^{*)}, 59K16B-1xx^{*)}

^{*)} -xx for all available cable variations

Packing

Standard	1500 pcs in box, 1500 pcs in reusable container (e)
Weight	1.48 g/pce

Coding

Part Number has to be accomplished by codification

Coding		Color	RAL	Part-Number
	A	black	sim. 9005	59Z113-000-A
	B	white	sim. 9001	59Z113-000-B
	C	blue	sim. 5005	59Z113-000-C
	D	bordeauxviolet	sim. 4004	59Z113-000-D
	E	green	sim. 6002	59Z113-000-E
	F	brown	sim. 8011	59Z113-000-F
	G	grey	sim. 7031	59Z113-000-G
	H	violet	sim. 4003	59Z113-000-H
	I	beige	sim. 1001	59Z113-000-I
	K	curry	sim. 1027	59Z113-000-K
	L	carmine red	sim. 3002	59Z113-000-L
	M	pastel orange	sim. 2003	59Z113-000-M
	N	pastel green	sim. 6019	59Z113-000-N
	Z	waterblue	sim. 5021	59Z113-000-Z
		traffic purple	sim. 4006	secondary lock

(g)

Change History

Rev.	Date	Change
e00	15.11.21	Packaging sizes updated -old packaging size “500 pcs in box, 1500 pcs in reusable container” -updated to “1500 pcs in box, 1500 pcs in reusable container” Changed font to non-italic
f00	26.04.23	Depictions of the two Variants of labeling added, on costumer request
g00	15.11.21	emoval of “on request” marker for L, M and N coding

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Lang	01.04.10	J. Schmid	13.09.24	g00	23-0775	L. Bartmann	24.07.23

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel. : +49 8684 18-0
Email : info@rosenberger.de

Page

3 / 3