





1203-021-A00E



.038 $\pm$.002
-.001 DIA.
3 WIRE HOLES



NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.
2. MATERIAL: BODY - BRASS PER ASTM B16
CENTER CONTACT - BRASS PER ASTM B16.
CONTACT FINGERS - BERYLLIUM COPPER PER ASTM B196.
INSULATOR - TEFLON PER ASTM D4894
CRIMP SLEEVE - D.H.P. COPPER CDA ALLOY 122
RETAINING RING - PHOSPHOR BRONZE PER QQ-B-750
GASKET - SILICONE RUBBER PER A-A-59588
3. FINISHES: RETAINING RING - NOT PLATED
CONTACT - GOLD PLATE PER ASTM B488
ALL OTHER METAL PARTS - SILVER PLATE PER ASTM B700

M39012/26-0012

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

TITLE: "TNC" CRIMP PLUG FOR RG-59B,
62A, 71B, 140B & 210/U CABLES

Drawn by BJM 1/28/05	Scale 4/1	Ckd. by MR	Engr Appd MR	FILE NAME: 1203021A00E-000T
----------------------------	--------------	---------------	-----------------	--------------------------------

CODE IDENT.-00795

1203-021-A00E

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ± 0.005 , 2 PLACES = ± 0.02 , ANGLES = $\pm 1/2^\circ$, SURFACE FINISH = 63

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.