





1310-013-K00E



NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.
2. MATERIAL: BODY - CORROSION RESISTANT STEEL PER ASTM A582
CONTACT - BERYLLIUM COPPER PER ASTM B196.
INSULATOR - TEFLON PER ASTM D4894
CRIMP SLEEVE - D.H.P. COPPER CDA ALLOY 122
3. FINISHES: CONTACTS - GOLD PLATE PER ASTM B488
BODY - PASSIVATE PER AMS-QQ-P-35
CRIMP SLEEVE - SULFAMATE NICKEL PER MIL-P-27418

-	OUTLINE	6/27/07
ALT.	REVISIONS	DATE

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ± 0.05 , 2 PLACES = ± 0.02 , ANGLES = $\pm 1/2^\circ$, SURFACE FINISH = 63

M39012/57-3028

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

TITLE: SMA CRIMP JACK FOR RG-55B, 142B
& 223/U CABLES - CAPTIVE CONTACT

Drawn by DG 6/27/07	Scale 4/1	Ckd. by MR	Engr Appd MR	FILE NAME: 1310013K00E-000T
---------------------------	--------------	---------------	-----------------	--------------------------------

CODE IDENT.-00795

1310-013-K00E

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED
OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.