


COAXIAL CONNECTOR, SK, 50 Ohm, Straight panel receptacle, jack (female), flange mount

23_SK-50-0-52/199_N

Properties

- The shortened male pin ensures a non-destructive mating process
- Particularly well suited for semi-rigid, semi-flex and flexible cable
- Mechanical intermateable with SMA and PC 3.5 (3.5 mm standard)



Product configuration

Interface type	Gender	Standard
SK	jack	MIL-STD-348A/323

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Stainless Steel	
Body	Stainless Steel	
Insulator	PPE (Polyphenylene ether, PPO)	

Electrical data

Impedance	50 Ω
Interface frequency	40 GHz

Mechanical data

Weight	0.0023 kg
Mating cycles	500
Flange type	2-hole flange / others
Tab style	Socket

Environmental data

Operation temperature	-40 °C ... 125°C
-----------------------	------------------

Ordering Information Table

Item number	Item description	Packaging type
22645977	23_SK-50-0-52/199_NE	Single

COAXIAL CONNECTOR, SK, 50 Ohm, Straight panel receptacle, jack (female), flange mount

23_SK-50-0-52/199_N

Additional Information	
Remarks	Hermetic sealed connector without glass bead supplement 73_Z-0-0-203 (1E-8 Torr l/s or cc/s at 1 atm), system leak rate dependent on customers process execution. For fixing hermetic seal while soldering, tool 74_Z-0-0-227 is recommended.

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2716 / Date of publication: 26.11.2023 / uncontrolled copy