

RG174, 50 Ohm, 1 GHz, 85°C, Ø2.8 mm, PVC jacket

RG_174_A/U

Properties

- Mil standard RG cable
- Excellent RF performance for precision applications
- Suitable for use in application up to 1 GHz



Construction			
Component	Material	Detail	Diameter
Centre conductor	Steel, Copper plated	Strand-07, 87%	0.48 mm - 0.12 mm
Dielectric	PE (Polyethylene)		1.48 mm
Outer conductor	Copper, Tin plated	Braid, 87%	2 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	2.8 mm +/- 0.12 mm

Electrical data	
Impedance	50 Ω +/-2Ω
Operating frequency	≤ 1 GHz
Capacitance	101 pF/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Screening effectiveness	40 dB at frequency 0.0001 GHz ... 1GHz
Insulation resistance	100000000 MΩ*m
Inner conductor resistance	317.3 Ω/km
Operating Voltage (at sea level)	≤ 1.5 kVrms
Test voltage (50 Hz/1 min)	≤ 3 kVrms

Mechanical data	
Weight	approx. 12 g/m
Static bending radius	≥ 15 mm
Repeated bending radius	28 mm
Dynamic bending radius	< 55 mm

RG174, 50 Ohm, 1 GHz, 85°C, Ø2.8 mm, PVC jacket

RG_174_A/U

Environmental data	
Operation temperature	-25 °C ... 85 °C
Installation temperature	-20 °C ... 60°C
Fire characteristics	contains halogene

Additional Information

MIL reference: M17/196-00001 (former reference: M17/119-RG174)

Suitable connectors

Cable group	U2
-------------	----

Ordering information

Item number	Item description	Available as assembly only
22511579	RG_174_A/U	No

Power MatrixCalculation: typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

a coefficient typical =	0.888	b coefficient typical =	0.034
fmax =	1.0	P at 1 GHz =	37.0
Frequency GHz	Nom. attenuation (dB/m)	Nom. attenuation (dB/ft)	CW power (W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.10	0.284	0.087	117
0.20	0.404	0.123	83
0.30	0.497	0.151	68
0.40	0.575	0.175	59
0.60	0.708	0.216	48
0.80	0.821	0.250	41
1.00	0.922	0.281	37

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P976 / Date of publication: 27.02.2024 / uncontrolled copy