

RG178, 50 Ohm, 3 GHz, 200°C, Ø1.8 mm, FEP jacket

RG_178_B/U

Properties

- Mil standard RG cable
- Excellent RF performance for precision applications
- Suitable for use in applications up to 3 GHz
- Extended temperature range



Construction			
Component	Material	Detail	Diameter
Centre conductor	Steel, Copper + Silver plated	Strand-07	0.31 mm
Dielectric	PTFE (Polytetrafluoroethylene)		0.83 mm
Outer conductor	Copper, Silver plated	Braid, 95%	1.33 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	1.8 mm +/- 0.1 mm

Electrical data	
Impedance	50 Ω +/-2Ω
Operating frequency	≤ 3 GHz
Capacitance	97 pF/m
Velocity of signal propagation	69 %
Signal delay	4.84 ns/m
Screening effectiveness	40 dB at frequency 0.0001 GHz ... 1GHz
Insulation resistance	100000000 MΩ*m
Inner conductor resistance	742 Ω/km
Operating Voltage (at sea level)	≤ 0.5 kVrms
Test voltage (50 Hz/1 min)	≤ 1 kVrms

Mechanical data	
Weight	approx. 8.4 g/m
Static bending radius	≥ 10 mm
Repeated bending radius	18 mm
Dynamic bending radius	< 27 mm

RG178, 50 Ohm, 3 GHz, 200°C, ø1.8 mm, FEP jacket
RG_178_B/U

Environmental data	
Operation temperature	-65 °C ... 200 °C
Installation temperature	-20 °C ... 60 °C
Flame propagation standard	IEC 60332-3
Fire characteristics	contains halogene

Additional Information
MIL reference: M17/93-RG178 and M17/93-00001

Suitable connectors	
Cable group	U1

Ordering information		
Item number	Item description	Available as assembly only
22510043	RG_178_B/U	No

Power Matrix			
Calculation: typical Attenuation [formula: (a*f^0.5 + b*f)] and maximum Power CW [formula: (p/f^0.5)]			
a coefficient typical =	1.414	b coefficient typical =	0.173
fmax =	3	P at 1 GHz =	52
Frequency	Nom. attenuation	Nom. attenuation	CW power
GHz	(dB/m)	(dB/ft)	(W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.20	0.667	0.203	116
0.40	0.963	0.294	82
0.60	1.199	0.365	67
0.80	1.403	0.428	58
1.00	1.587	0.484	52
1.20	1.757	0.535	47
1.40	1.915	0.584	44
1.60	2.065	0.630	41
1.80	2.208	0.673	39
2.00	2.346	0.715	37
3.00	2.968	0.905	30

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P974 / Date of publication: 08.08.2024 / uncontrolled copy