

RG59, 75 Ohm, 1 GHz, 85°C, Ø6.1 mm, PVC jacket

RG_59_B/U

Properties

- Mil standard RG cable
- Excellent RF performance for precision applications
- Suitable for use in application up to 1 GHz
- 75 Ohm characteristic Impedance



Construction			
Component	Material	Detail	Diameter
Centre conductor	Steel, Copper plated	Wire, 93%	0.58 mm - 0.15 mm
Dielectric	PE (Polyethylene)		3.64 mm
Outer conductor	Copper	Braid, 93%	4.5 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	6.1 mm +/- 0.15 mm

Electrical data	
Impedance	75 Ω +/-1.5Ω
Operating frequency	≤ 1 GHz
Capacitance	67 pF/m
Velocity of signal propagation	66 %
Signal delay	5.07 ns/m
Screening effectiveness	40 dB at frequency 0.0001 GHz ... 1GHz
Insulation resistance	100000000 MΩ*m
Inner conductor resistance	152 Ω/km
Operating Voltage (at sea level)	≤ 3 kVrms
Test voltage (50 Hz/1 min)	≤ 6 kVrms

Mechanical data	
Weight	approx. 50 g/m
Static bending radius	≥ 35 mm
Repeated bending radius	65 mm

Environmental data	
Operation temperature	-25 °C ... 85 °C
Installation temperature	-20 °C ... 60 °C
Fire characteristics	contains halogene

RG59, 75 Ohm, 1 GHz, 85°C, Ø6.1 mm, PVC jacket
RG_59_B/U

Additional Information		
MIL reference: M17/184-00001 (former reference: M17/29-RG59)		

Suitable connectors	
Cable group	U16

Ordering information		
Item number	Item description	Available as assembly only
22510368	RG_59_B/U	No

Power Matrix			
Calculation: typical Attenuation [formula: (a*f^0.5 + b*f)] and maximum Power CW [formula: (p/f^0.5)]			
a coefficient typical =	0.3173	b coefficient typical =	0.0499
fmax =	1.0	P at 1 GHz =	101.0
Frequency	Nom. attenuation	Nom. attenuation	CW power
GHz	(dB/m)	(dB/ft)	(W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.10	0.105	0.032	319
0.20	0.152	0.046	226
0.30	0.189	0.058	184
0.40	0.221	0.067	160
0.60	0.276	0.084	130
0.80	0.324	0.099	113
1.00	0.367	0.112	101

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P954 / Date of publication: 08.08.2024 / uncontrolled copy