

Product data sheet

Specifications



encoder cable 3m shielded, leads connection for BCH2.B/.D/.F, CN2 plug

VW3M8D1AR30

Main

Range of product	Lexium
Accessory / separate part category	Connection accessories
Accessory / separate part type	Encoder cable
Product or component type	Encoder cable
Device application	For BCH2 with SinCos single turn encoder
Accessory / separate part destination	From servo motor to servo drive
Cable composition	5 x (2 x 0.13 mm²)

Complementary

Electrical connection	1 connector Firewire 6 pin(s) 1 connector Molex 9 pin(s)
Range compatibility	Lexium 28
Cable length	3 m
Product weight	1 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	29.000 cm
Package 1 Length	25.000 cm
Package 1 Weight	134.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.715 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

 Repack and remanufacture	
Take-back	No