



Manual Starter, fractional horsepower, 16A, 2 poles, 1 HP at 277 VAC, toggle operated, no indicator, NEMA 1 enclosure

2510FG2

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Single Unit Manual Starter	
Туре	F	
Overload Relay Type	Melting alloy	

Complementary

Current Rating	16 A	
cable entry	0.5" and 0.75" knock-outs (top and bottom)	
Horsepower Rating	1 hp 115 V AC 1 hp 277 V AC 0.75 hp 115 V DC 0.75 hp 230 V DC 2 hp 230 V AC	
Voltage Rating	277 V AC 230 V DC	
Number of Poles	2P	
Control Unit	Toggle switch	
Number of Phases	1 phase	
Pilot Light	No indicator	
Reset	Manual	
Motor starter type	Non reversing	
Electrical Connection	Screw clamp terminals	
Wire Gauge	AWG 14AWG 12 copper	
Height	4.25 in (107.95 mm)	
Width	2.44 in (61.98 mm)	
Depth	2.75 in (69.85 mm)	
Net Weight	0.79 lb(US) (0.36 kg)	

Environment

Product Certifications	UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05
NEMA Enclosure Rating	NEMA 1 Plastic standard size

Ordering and shipping details

Category US10CP121101

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule	0CP1
GTIN	785901553953
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	2.60 in (6.604 cm)	
Package 1 Width	3.00 in (7.62 cm)	
Package 1 Length	4.70 in (11.938 cm)	
Package weight(Lbs)	12.640 oz (358.338 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	14	
Package 2 Height	8.90 in (22.606 cm)	
Package 2 Width	8.30 in (21.082 cm)	
Package 2 Length	14.50 in (36.83 cm)	
Package 2 Weight	11.680 lb(US) (5.298 kg)	
Unit Type of Package 3	PAL	
Number of Units in Package 3	624	
Package 3 Height	40.00 in (101.6 cm)	
Package 3 Width	40.00 in (101.6 cm)	
Package 3 Length	48.00 in (121.92 cm)	
Package 3 Weight	493.0003 lb(US) (223.621 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better


Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

○ Repack and remanufacture	
Take-back	No


Technical Illustration

Dimensions



Technical Illustration

Wiring diagram



REFER TO INSTRUCTION SHEET AND TECHNICAL DOCUMENTATION FOR COMPLETE INFORMATION