

Climasys CC - electronic hygrotherm - 95 to 135V - temp -40 to 80 C - Hr 20 to 80%

NSYCCOHYT120VID

Overview

Lead time Usually Ships within 4 Weeks

Main

Range	ClimaSys	
Product name	ClimaSys CC	
Product or component type	Electronic hygrotherm	
Temperature setting range	-4080 °C	
Humidity setting range	2080 %	
Display type	OLED screen	
Information displayed	Temperature in °F Relative humidity Temperature in °C	

Complementary

90140 V AC	
Optional NTC external sensor	
4 A 120 V AC	
8 connectors, clamping capacity: 2.5 mm²	
By screws Clipped	
External: 85 mm	
External: 56 mm	
External : 44 mm	
35 mm DIN rail Cross rails On mounting plate Spacial upright	
-4080 °C	
2 K programmed value	
3 %	
2 ventilation/heating function	
PC	
Light grey	
Self-extinguishing conforming to UL94 (material V0)	

Product certifications UR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	5.000 cm
Package 1 Length	4.500 cm
Package 1 Weight	180.000 g

Contractual warranty

Coverage	Core product
Warranty	18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	3452f1a3-f13d-4adf-84ba-2572bcc8e35c
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins