



Main

Range	TeSys
Product name	TeSys GC
Product or Component Type	Modular contactor
Device short name	GC63
Contactor application	Motor control Lighting Heating

Complementary

Utilisation category	AC-7B AC-7A
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	≤ 250 V AC
[Ie] rated operational current	63 A AC-7A 25 A AC-7B
Operating position	30°/vertical
Control circuit type	AC 60 Hz
[Uc] control circuit voltage	220...240 V AC 60 Hz
[Uimp] rated impulse withstand voltage	4 kV
[Ith] conventional free air thermal current	63 A 122 °F (50 °C) power circuit
Irms rated making capacity	200 A 400 V AC power circuit IEC 61095
Rated breaking capacity	200 A 400 V power circuit IEC 61095
[Icw] rated short-time withstand current	504 A 104 °F (40 °C) - 10 s power circuit 157 A 104 °F (40 °C) - 30 s power circuit
Associated fuse rating	63 A gL ≤ 440 V power circuit
Average impedance	2 mOhm - Ith 63 A 50 Hz power circuit
[Ui] rated insulation voltage	500 V IEC 61095 500 V VDE 0110
Electrical durability	AC-7A 100000 cycles AC-7B 100000 cycles
Power dissipation per pole	8 W
Control Type	Remote control
Mounting Mode	Clip-on
Mounting Support	DIN rail
Standards	IEC 60947-5 IEC 61095

Connections - terminals	Control circuit screw clamp terminals 1 0.00 in ² (2.5 mm ²)flexible without cable end Control circuit screw clamp terminals 2 0.00 in ² (2.5 mm ²)flexible without cable end Control circuit screw clamp terminals 1 0.00 in ² (2.5 mm ²)flexible with cable end Control circuit screw clamp terminals 2 0.00 in ² (1.5 mm ²)flexible with cable end Control circuit screw clamp terminals 1 0.00 in ² (1.5 mm ²)solid without cable end Control circuit screw clamp terminals 2 0.00 in ² (1.5 mm ²)solid without cable end Power circuit screw clamp terminals 1 0.04 in ² (25 mm ²)flexible without cable end Power circuit screw clamp terminals 2 0.02 in ² (16 mm ²)flexible without cable end Power circuit screw clamp terminals 1 0.02 in ² (16 mm ²)flexible with cable end Power circuit screw clamp terminals 2 0.01 in ² (4 mm ²)flexible with cable end Power circuit screw clamp terminals 1 0.04 in ² (25 mm ²)solid without cable end Power circuit screw clamp terminals 2 0.01 in ² (6 mm ²)solid without cable end
Tightening torque	Control circuit 7.08 lbf.in (0.8 N.m) screw clamp terminals Power circuit 17.70 lbf.in (2 N.m) screw clamp terminals
Operating time	10...25 ms opening 10...30 ms closing
Mechanical durability	1000000 cycles
Maximum operating rate	300 cyc/h 122 °F (50 °C)
Control circuit voltage limits	Drop-out 0.2...0.75 Uc 50 Hz 122 °F (50 °C)) Operational 0.85...1.1 Uc 50 Hz 122 °F (50 °C))
Inrush power in VA	53 VA 50 Hz 68 °F (20 °C))
Hold-in power consumption in VA	6.5 VA 50 Hz 68 °F (20 °C))
Heat dissipation	2.1 W 50/60 Hz

Environment

IP degree of protection	IP40 VDE 0106 in enclosure) IP20 VDE 0106
Protective treatment	TC
Ambient Air Temperature for Operation	23...122 °F (-5...50 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Operating altitude	<= 9842.52 ft (3000 m)
Mechanical robustness	Shocks contactor open10 Gn for 11 ms Shocks contactor closed15 Gn for 11 ms Vibrations contactor open2 Gn, 5...300 Hz Vibrations contactor closed3 Gn, 5...300 Hz
Total number of 18 mm modules	3
Height	3.35 in (85 mm)
Width	2.13 in (54 mm)
Depth	2.46 in (62.5 mm)
Product Weight	0.86 lb(US) (0.39 kg)
Quantity per Set	Set of 4
Color	White

Ordering and shipping details

Category	22621 - IEC PANEL ACCESSORIES
Discount Schedule	I
GTIN	3389118090705
Nbr. of units in pkg.	1
Package weight(Lbs)	11.64 oz (330 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.15 in (8 cm)
Package 1 width	3.74 in (9.5 cm)
Package 1 Length	9.06 in (23 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	4

Package 2 Weight	2.91 lb(US) (1.322 kg)
Package 2 Height	3.15 in (8 cm)
Package 2 width	3.74 in (9.5 cm)
Package 2 Length	9.06 in (23 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------