

IEC contactor, Easy TeSys DPE, nonreversing, 32A, 3P, 15HP at 480V AC, 240V 50/60Hz coil

DPE32U7

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Easy TeSys	
Product name	Easy TeSys DPE	
Product or Component Type	Contactor	
Device short name	DPE	
Contactor application	Resistive load Motor control	
Utilisation category	AC-4 AC-1 AC-3	
Poles description	3P	
Pole contact composition	3 NO	
Auxiliary contact composition	1 NO	
[le] rated operational current	32 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 40 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit	
[Uc] control circuit voltage	240 V AC 50/60 Hz	
Motor power kW	7.5 kW 220230 V AC 50/60 Hz 15 kW 380400 V AC 50/60 Hz 15 kW 415 V AC 50/60 Hz 15 kW 440 V AC 50/60 Hz 18.5 kW 500 V AC 50/60 Hz 18.5 kW 660690 V AC 50/60 Hz	
Maximum Horse Power Rating	2 hp at 115 V AC 50/60 Hz for 1 phase motors 3 hp at 230/240 V AC 50/60 Hz for 1 phase motors 7.5 hp at 200/208 V AC 50/60 Hz for 3 phase motors 7.5 hp at 230/240 V AC 50/60 Hz for 3 phase motors 15 hp at 460/480 V AC 50/60 Hz for 3 phase motors 20 hp at 575/600 V AC 50/60 Hz for 3 phase motors	

Complementary

Maximum Operational Voltage	Power circuit <= 690 V AC 25400 Hz	
	Power circuit <= 300 V DC	
[Ith] conventional free air thermal	10 A (at 140 °F (60 °C)) for signalling circuit	
current	40 A (at 140 °F (60 °C)) for power circuit	
Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1	
	250 A DC for signalling circuit conforming to IEC 60947-5-1	
	450 A at 440 V for power circuit conforming to IEC 60947	
Rated breaking capacity	450 A at 440 V for power circuit conforming to IEC 60947	
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1	
	63 A gG at <= 690 V coordination type 1 for power circuit	
	40 A gG at <= 690 V coordination type 2 for power circuit	
Average impedance	2 mOhm - Ith 40 A 50 Hz for power circuit	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Power dissipation per pole		
	3.2 W AC-1 1.25 W AC-3	
Electrical durability	1 Mcycles 32 A AC-3 <= 440 V 0.6 Mcycles 40 A AC-1 <= 440 V	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1	
Control circuit type	AC 50/60 Hz	
Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <158 °F (70 °C)) Operational: 0.81.1 Uc at 50 Hz (at <140 °F (60 °C)) Operational: 0.851.1 Uc at 60 Hz (at <140 °F (60 °C)) Operational: 11.1 Uc at 50/60 Hz (at <158 °F (70 °C))	
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))	
Hold-in power consumption in VA	7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))	
Heat dissipation	23 W 50/60 Hz	
Operating time	1222 ms closing 419 ms opening	
Mechanical durability	10 Mcycles	
Maximum operating rate	3600 cyc/h 140 °F (60 °C)	
Auxiliary contacts type	Mechanically linked 1 NO IEC 60947-5-1	
Minimum switching current	5 mA for signalling circuit	
Minimum switching voltage	17 V for signalling circuit	
Insulation resistance	> 10 MOhm for signalling circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Signalling circuit frequency	25400 Hz	
Connections - terminals	Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness:	
	flexible without cable end Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable	
Tightening torque	Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end	
Tightening torque Mounting Support	Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2 Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm	

Width	1.8 in (45 mm)
Depth	3.6 in (92 mm)
Net Weight	0.82 lb(US) (0.37 kg)

Environment

Livitoiiiieit		
[Ui] rated insulation voltage	Power circuit 690 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 690 V IEC 60947-1	
Overvoltage category	III	
Pollution degree	3	
[Uimp] rated impulse withstand voltage	6 kV IEC 60947	
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 60947-4-1	
Product Certifications	UL CSA CCC CE	
IP degree of protection	IP20 front face IEC 60529	
Ambient Air Temperature for Storage	-76176 °F (-6080 °C)	
Ambient Air Temperature for Operation	-40140 °F (-4060 °C)	
Operating altitude	06561.68 ft (02000 m)	
Fire resistance	1562 °F (850 °C) IEC 60695-2-1	
Mechanical robustness	Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms)	

Ordering and shipping details

Category	US10I1322362	
Discount Schedule	0113	
GTIN	3606481063250	
Returnability	Yes	
Country of origin	ID	

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.20 in (5.59 cm)
Package 1 Width	3.80 in (9.65 cm)
Package 1 Length	4.70 in (11.94 cm)
Package weight(Lbs)	0.93 lb(US) (0.42 kg)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	26
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use Again

☼ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative







