

Head for illuminated selector switch, Harmony XB5, Harmony XALF, grey plastic, green handle, 22mm, universal LED, 2 positions

ZB5AK1233

Product availability: Stock - Normally stocked in distribution facility

Important message: A change in appearance may be noted on the product but does not affect its use in terms of function and safety. This makes it compatible with our Universal LED blocks

Main

Range of Product	Harmony XB5 Harmony XALF		
Product or Component Type	Head for illuminated selector switch		
Product Compatibility	Universal LED		
Device short name	ZB5		
Bezel material	Dark grey plastic		
Mounting diameter	0.9 in (22 mm)		
Head type	Standard		
Sale per indivisible quantity	1		
Shape of signaling unit head	Round		
Type of operator	stay put		
Operator profile	Green standard handle		
Operator position information	2 positions 90°		

Complementary

CAD overall width	1.1 in (29 mm)		
CAD overall height	1.1 in (29 mm)		
CAD overall depth	1.7 in (43 mm)		
Product Weight	0.035 lb(US) (0.016 kg)		
Mechanical durability	1000000 cycles		
Station name	XALD 15 cut-outs XALK 25 cut-outs		
Electrical composition code	M3 4 single front mounting integral LED M6 2 single front mounting integral LED and transformer M10 2 single front mounting integral LED MF1 2 single front mounting integral LED MR1 2 single rear mounting integral LED M4 4 single and double front mounting integral LED		
Device presentation	Basic element		

Environment

		T11
rotective	treatment	IH

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Storage	-40158 °F (-4070 °C)		
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)		
Overvoltage category	Class II conforming to IEC 60536		
IP degree of protection	IP66 IEC 60529		
	IP67		
	IP69		
	IP69K		
NEMA degree of protection	NEMA 13		
	NEMA 4X		
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131 °F (55 °C) 0.1 m		
IK degree of protection	IK04 conforming to IEC 50102		
Standards	UL 508		
	CSA C22.2 No 14		
	JIS C8201-5-1		
	EN/IEC 60947-5-5		
	EN/IEC 60947-5-1		
	EN/IEC 60947-5-4		
	EN/IEC 60947-1		
	JIS C8201-1		
Product Certifications	CSA		
	DNV		
	BV		
	LROS (Lloyds register of shipping)		
	UL Listed		
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6		
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27		
	50 gn 11 ms) half sine wave acceleration IEC 60068-2-27		

Ordering and shipping details

	· · · · · · · · · · · · · · · · · · ·	
Category	US10CS222467	
Discount Schedule	0CS2	
GTIN	3389110906066	
Returnability	Yes	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	2.24 in (5.700 cm)	
Package 1 Width	2.05 in (5.200 cm)	
Package 1 Length	1.30 in (3.300 cm)	
Package weight(Lbs)	0.811 oz (23.000 g)	
Unit Type of Package 2	S03	
Number of Units in Package 2	200	
Package 2 Height	11.81 in (30.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	11.572 lb(US) (5.249 kg)	
Unit Type of Package 3	P06	

Number of Units in Package 3	1600	
Package 3 Height	29.53 in (75.000 cm)	
Package 3 Width	23.62 in (60.000 cm)	
Package 3 Length	31.50 in (80.000 cm)	
Package 3 Weight	115.972 lb(US) (52.604 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No

ZB5AK1233

Dimensions Drawings


Dimensions



Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)


Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3) Ø22.5 mm recommended (Ø22.3 $_0^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 in. $_0^{+0.016}$)

				0
Connections	a in mm	a in in.	b in mm	b in in.
By screw clamp terminals or plug-in connector	40	1.57	30	1.18
By Faston connectors	45	1.77	32	1.26
On printed circuit board	30	1.18	30	1.18


Detail of Lug Recess



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3) Ø22.5 mm recommended (Ø22.3 $_0^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 in. $_0^{+0.016}$)

Pushbuttons, Switches and Pilot Lights for Printed Circuit Board Connection


Panel Cut-outs (Viewed from Installer's Side)




A: 30 mm min. / 1.18 in. min. **B:** 40 mm min. / 1.57 in. min.

Printed Circuit Board Cut-outs (Viewed from Electrical Block Side)

Dimensions in mm



A: 30 mm min. B: 40 mm min. Dimensions in in.



A: 1.18 in. min. **B:** 1.57 in. min.


General Tolerances of the Panel and Printed Circuit Board

The cumulative tolerance must not exceed 0.3 mm / 0.012 in.: T1 + T2 = 0.3 mm max.

Installation Precautions

- Minimum thickness of circuit board: 1.6 mm / 0.06 in.
- Cut-out diameter: 22.4 mm ± 0.1 / 0.88 in. ± 0.004
- Orientation of body/fixing collar ZB5AZ009: ± 2°30' (excluding cut-outs marked **a** and **b**).
- Tightening torque of screws ZBZ006: 0.6 N.m (5.3 lbf.in) max.
- Allow for one ZB5AZ079 fixing collar/pillar and its fixing screws:
 - $_{\circ}$ every 90 mm / 3.54 in. horizontally (X), and 120 mm / 4.72 in. vertically (Y).
 - o with each selector switch head (ZB5AD•, ZB5AJ•, ZB5AG•).

The fixing centers marked ${\bf a}$ and ${\bf b}$ are diagonally opposed and must align with those marked ${\bf 4}$ and ${\bf 5}$.



ZB5AK1233

- (1) Head ZB5AD•
- (2) Panel
- (2) Nut
- (4) Printed circuit board

Mounting of Adapter (Socket) ZBZ01•


- 1 2 elongated holes for ZBZ006 screw access
- $_{\bullet}$ 2 1 hole Ø 2.4 mm ± 0.05 / 0.09 in. ± 0.002 for centring adapter ZBZ01 $\!\!^{\bullet}$
- 3 8 × Ø 1.2 mm / 0.05 in. holes
- 4 1 hole Ø 2.9 mm ± 0.05 / 0.11 in. ± 0.002, for aligning the printed circuit board (with cut-out marked a)
- 5 1 elongated hole for aligning the printed circuit board (with cut-out marked b)
- 6 4 holes Ø 2.4 mm / 0.09 in. for clipping in adapter ZBZ01•

Dimensions An + 18.1 relate to the Ø 2.4 mm \pm 0.05 / 0.09 in. \pm 0.002 holes for centring adapter ZBZ01•.

ZB5AK1233

Technical Description

Electrical Composition Corresponding to Code M3



Electrical Composition Corresponding to Code M4



Electrical Composition Corresponding to Codes M6 and P2



ZB5AK1233

Electrical Composition Corresponding to Codes M5, M10, MF1, MR1 and MF2



Legend

Single contact



Double contact



Light block



Possible location



Sequence of Contacts Fitted to 2-position Selector Switch Body

Position 315°



	Position	Тор		П	
Push	T GOILLOIT	Bottom			\triangle
	Location		Left		Right
	State		0		0
Contacts	N/O		open		open
Contacts	N/C		closed		closed


Position 45°



Push	Position	Тор			
		Bottom			
	Location		Left	\otimes	Right
	State		1		1
Contacts	N/O		closed		closed
	N/C		open		open

Technical Illustration

Dimensions



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB5



Aug 30, 2025

Image of product / Alternate images

Alternative











