

Terminal block, Linergy TR, clip on mounting, splitter block

AB3RV162U

Complementary

[In] rated current	150 A for 1P busbar	
Electrical connection	1 solid upstream 35 mm² connector 1 flexible upstream 25 mm² connector 6 solid downstream 0.56 mm² tap-off 6 flexible downstream 0.54 mm² tap-off	
fixing mode	Clip-on	
Mounting support	rail	
Product compatibility	Universal fixing frames	
Product destination	terminal block	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.500 cm
Package 1 Width	12.700 cm
Package 1 Length	7.750 cm
Package 1 Weight	91.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	13.500 cm
Package 2 Width	12.700 cm
Package 2 Length	15.500 cm
Package 2 Weight	917.000 g
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Height	15.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	3.970 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No