



Overview

Presentation	APC Smart-UPS SC is ideal for small and medium businesses looking to protect networking equipment and point-of-sale (POS) devices from power disturbances and outages. The Smart-UPS SC features network grade protection, hot swap batteries, and built-in data line protection for worry free uninterruptible power protection for increased availability. Built on the same standards as the award-winning Smart-UPS, Smart-UPS SC provides the basic features and manageability needed to protect entry-level applications
Lead time	Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	390 W
Rated power in VA	620 VA
Plug standard	NEMA 5-15P
Nb of power socket outlets	4 NEMA 5-15R
Cable length	6 ft (1.83 m)
Number of cables	1
Battery type	Lead-Acid battery
Provided equipment	User Manual Smart UPS signalling RS-232 cable CD with software

General

Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	Entry level
Redundant	No

Physical

Color	Gray
Height	6.61 in (16.8 cm)
Width	4.69 in (11.9 cm)
Depth	14.49 in (36.8 cm)
Net Weight	27.07 lb(US) (12.28 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Efficiency at full load	75...154 V adjustable 82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Maximum configurable power in VA	620 VA
Max Configurable Power (Watts)	390 W
Transfer Time	4ms typical : 8ms maximum
Topology	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications	CSA
Equipment protection policy	Lifetime : \$150000
Standards	FCC Part 15 class A UL 1778

Environmental

Acoustic level	45 dBA
Heat dissipation	70 Btu/h
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Batteries & Runtime

Battery Voltage	12 V
Extendable Run Time	0
Battery capacity	12.0 Ah
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	5 h
RBC Quantity	1
Battery life	3...5 year(s)
Battery power in VAh	132 VAh runtime
Battery Charge Power (Watts)	26 W rated

Communications & Management

Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Emergency Power Off (EPO)	Optional
Free slots	0

Surge Protection and Filtering

Data line protection	RJ45 Modem/Fax/DSL/10-100 Base-T protection
Surge energy rating	412 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304222620
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	PH

Packing Units

Package 1 Height	12.52 in (31.8 cm)
Package 1 width	10.31 in (26.2 cm)
Package 1 Length	20.00 in (50.8 cm)
Number of Units in Package 3	12

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------