

# Motor circuit breaker, TeSys Deca, 3P, 80A, Icu 100kA, thermal magnetic, multifunction, UL489

GV4PB80S

Product availability: Stock - Normally stocked in distribution facility

## Main

Range of Product	TeSys GV4	
Range	TeSys Deca	
Device short name	GV4PB	
product name	TeSys GV4	
Product or Component Type	Motor circuit breaker	
Device Application	Motor protection	
Trip unit technology	Thermal-magnetic Electronic	

## Complementary

Poles description	3P	
Utilisation category	Category A IEC 60947-2 AC-3 IEC 60947-4-1	
Operating position	Any position	
Breaking capacity	100 kA SCCR 240 V AC 60 Hz UL 489 65 kA SCCR 480Y/277 V AC 60 Hz UL 489 25 kA SCCR 600Y/347 V AC 60 Hz UL 489 120 kA Icu 220/240 V AC 50/60 Hz IEC 60947-2 100 kA Icu 380/415 V AC 50/60 Hz IEC 60947-2 70 kA Icu 440 V AC 50/60 Hz IEC 60947-2 30 kA Icu 500 V AC 50/60 Hz IEC 60947-2 18 kA Icu 525 V AC 50/60 Hz IEC 60947-2 10 kA Icu 660/690 V AC 50/60 Hz IEC 60947-2	
[Ics] rated service short-circuit breaking capacity	100 % 220/240 V AC 50/60 Hz IEC 60947-2 100 % 380/415 V AC 50/60 Hz IEC 60947-2 100 % 440 V AC 50/60 Hz IEC 60947-2 100 % 500 V AC 50/60 Hz IEC 60947-2 100 % 525 V AC 50/60 Hz IEC 60947-2 25 % 660/690 V AC 50/60 Hz IEC 60947-2	
Control Type	Toggle	
Line Rated Current	80 A	
Magnetic tripping current	1360 A	
[Ue] rated operational voltage	690 V AC 50/60 Hz IEC 60947-2 600Y/347 V AC 60 Hz UL 489	
[Ui] rated insulation voltage	800 V AC 50/60 Hz IEC 60947-2	
[Ith] conventional free air thermal current	1 115 A IEC 60947-4-1	
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2	
Power dissipation per pole	4.6 W	
Mechanical durability	40000 cycles	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electrical durability	14000 cycles AC-3 440 V In/2 7000 cycles AC-3 440 V In	
Maximum operating rate	25 cyc/h	
Rated duty	Continuous IEC 60947-4-1	
Connections - terminals	EverLink BTR screw connectors top) 1 0.0020.1 in² (1.570 mm²) - rigid EverLink BTR screw connectors top) 1 0.0020.08 in² (1.550 mm²) - flexible EverLink BTR screw connectors bottom) 1 0.0040.1 in² (2.595 mm²) - rigid EverLink BTR screw connectors bottom) 1 0.0040.1 in² (2.570 mm²) - flexible	
Tightening torque	79.7 lbf.in (9 N.m) 0.020.1 in² (1695 mm²) 44.3 lbf.in (5 N.m) 0.0020.02 in² (1.510 mm²)	
Mechanical robustness	Vibrations +/- 1 mm 213.2 Hz IEC 60068-2-6 Vibrations 0.7 gn 13.2100 Hz IEC 60068-2-6 Shocks 15 gn 11 ms IEC 60068-2-27	
Phase failure sensitivity	Yes IEC 60947-4-1	
Height	6.7 in (171 mm)	
Width	3.2 in (81 mm)	
Depth	4.6 in (116 mm)	
Net Weight	3.20 lb(US) (1.45 kg)	
color	Gray RAL 7016)	
Suitability for isolation	Yes IEC 60947-1	

## **Environment**

Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-4-1 UL 489 CSA C22.2 No 5	
Product Certifications	IEC UL CSA	
Climatic withstand	IACS E10	
IK degree of protection	IK07 IEC 62262	
pollution degree	3	
IP degree of protection	IP40 IEC 60529	
Ambient Air Temperature for Storage	-58185 °F (-5085 °C)	
Fire resistance	1760 °F (960 °C) IEC 60695-2-11	
Operating altitude	5000 m	
Ambient air temperature for operation	-13158 °F (-2570 °C)	

# Ordering and shipping details

Category	US10I1122365
Discount Schedule	0111
GTIN	3606489868697
Returnability	Yes
Country of origin	PL

# **Packing Units**

Unit Type of Package 1 PCE
----------------------------

Number of Units in Package 1	1	
Package 1 Height	4.92 in (12.5 cm)	
Package 1 Width	3.54 in (9.0 cm)	
Package 1 Length	8.88 in (22.55 cm)	
Package 1 Weight	3.821 lb(US) (1.733 kg)	
Unit Type of Package 2	S03	
Number of Units in Package 2	5	
Package 2 Height	11.81 in (30.0 cm)	
Package 2 Width	11.81 in (30.0 cm)	
Package 2 Length	15.75 in (40.0 cm)	
Package 2 Weight	20.9 lb(US) (9.5 kg)	

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	91
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1b259a2c-3a3c-401a-acdd-f0837efd4018
REACh Regulation	REACh Declaration
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

#### Offer Marketing Illustration

#### Product benefits / Features



#### Offer Marketing Illustration

#### **Product benefits / Features**



#### Offer Marketing Illustration

#### **Product benefits / Features**



### **Technical Illustration**

### Assembly's dimensions



