

Illuminated double headed push button, Harmony XB5, plastic, 22mm, 1 green flush I + 1 pilot light + 1 red projecting O, 1 NO + 1 NC

XB5AW73731B5

Product availability: Non-Stock - Not normally stocked in distribution facility

Important message: A change in appearance may be noted on the product but does not affect its use in terms of function and safety. This makes it compatible with our Universal LED blocks

Main

Range of Product	Harmony XB5				
Product or Component Type	Illuminated double-headed push-button				
Device short name	XB5				
Bezel material	Dark grey plastic				
Fixing collar material	Plastic				
Head type	Standard				
Mounting diameter	0.9 in (22 mm)				
Shape of signaling unit head	Rectangular				
Type of operator	spring return				
Operator profile	1 flush - 1 projecting push-buttons - 1 central pilot light				
Operators description	Green "I" - red "O"				
Contacts type and composition	1 NO + 1 NC				
Contact operation	Slow-break				
Connections - terminals	Screw clamp terminals, <= 2 x 1.5 mm² with cable end IEC 60947-1 Screw clamp terminals, >= 1 x 0.22 mm² without cable end IEC 60947-1 Spring terminals, <= 2 x 1.5 mm² with cable end IEC 60947-1 Spring terminals, >= 1 x 0.22 mm² without cable end IEC 60947-1				
Light source	Protected LED				
Bulb base	Integral LED				
[Us] rated supply voltage	24 V AC/DC 50/60 Hz				

Complementary

Height	2.0 in (50 mm)	
Width	1.2 in (30 mm)	
Depth	2.3 in (59 mm)	
Terminals description ISO n°1	(11-12)NC (13-14)NO	
Net Weight	0.146 lb(US) (0.066 kg)	
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131 °F (55 °C) 0.1 m	
Colour of marking	Black marking when white caps White marking when green, red or black caps	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Operator profile	Green flush, I white) Red projecting, O white)			
Contacts usage	Standard contacts			
Positive opening	With IEC 60947-5-1 appendix K			
Operating travel	0.06 in (1.5 mm) NC changing electrical state) 0.1 in (2.6 mm) NO changing electrical state) 0.2 in (4.3 mm) total travel)			
Operating force	3.5 N NC changing electrical state 3.8 N NO changing electrical state			
Mechanical durability	1000000 cycles			
Tightening torque	7.0810.6 lbf.in (0.81.2 N.m) IEC 60947-1			
Shape of screw head	Cross JIS No 1 Cross Philips no 1 Cross pozidriv No 1 Slotted flat Ø 4 mm Slotted flat Ø 5.5 mm			
Contacts material	Silver alloy (Ag/Ni)			
Short-circuit protection	10 A cartridge fuse gG IEC 60947-5-1			
[Ith] conventional free air thermal current	10 A IEC 60947-5-1			
[Ui] rated insulation voltage	600 V 3)IEC 60947-1			
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-1			
[le] rated operational current	3 A 240 V, AC-15, A600 IEC 60947-5-1 6 A 120 V, AC-15, A600 IEC 60947-5-1 0.1 A 600 V, DC-13, Q600 IEC 60947-5-1 0.27 A 250 V, DC-13, Q600 IEC 60947-5-1 0.55 A 125 V, DC-13, Q600 IEC 60947-5-1 1.2 A 600 V, AC-15, A600 IEC 60947-5-1			
Electrical durability	1000000 cycles, AC-15, 2 A 230 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 3 A 120 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 4 A 24 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.2 A 110 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.5 A 24 V 3600 cyc/h 0.5 IEC 60947-5-1 appendix C			
Electrical reliability	Λ < 10exp(-6) 5 V 1 mA in clean environment IEC 60947-5-4 Λ < 10exp(-8) 17 V 5 mA in clean environment IEC 60947-5-4			
Signalling type	Steady			
Light source colour	White			
Supply voltage limits	19.230 V DC 21.626.4 V AC			
Current Consumption	18 mA			
Service life	100000 year(s) at rated voltage and 25 °C			
Surge withstand	1 kV IEC 61000-4-5			
Device presentation	Complete product			
Environment				
Protective treatment	тн			
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)			
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)			
Overvoltage category	Class II conforming to IEC 61140			
IP degree of protection	IP66 IEC 60529 IP69 IEC 60529 IP69K			

IP69K

NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK05 conforming to IEC 50102
Standards	IEC 60947-5-1 UL 508 IEC 60947-1
	JIS C8201-5-1 CSA C22.2 No 14 IEC 60947-5-4 JIS C8201-1
Product Certifications	CSA LROS (Lloyds register of shipping) BV UL Listed DNV
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27
Resistance to fast transients	2 kV IEC 61000-4-4
Resistance to electromagnetic fields	9.1 V/m (10 V/m) IEC 61000-4-3
Resistance to electrostatic discharge	6 kV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2
Electromagnetic emission	Class B IEC 55011

Ordering and shipping details

Category	US10CS222467
Discount Schedule	0CS2
GTIN	3389119043540
Returnability	Yes
Country of origin	FR

Packing Units

_		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.39 in (8.600 cm)	
Package 1 Width	1.30 in (3.300 cm)	
Package 1 Length	2.09 in (5.300 cm)	
Package 1 Weight	2.152 oz (61.000 g)	
Unit Type of Package 2	S03	
Number of Units in Package 2	100	
Package 2 Height	11.81 in (30.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	14.491 lb(US) (6.573 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	800	
Package 3 Height	29.53 in (75.000 cm)	

Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	139.606 lb(US) (63.324 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	20
Environmental Disclosure	Product Environmental Profile

Use Better


Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	1b727668-980f-44dd-96d8-f205d181f25e
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Dimensions Drawings

Dimensions



e: clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.


Product data sheet

XB5AW73731B5

Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)


Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3) Ø22.5 mm recommended (Ø22.3 $_0^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 in. $_0^{+0.016}$)

				-
Connections	a in mm	a in in.	b in mm	b in in.
By screw clamp terminals or plug-in connector	40	1.57	30	1.18
By Faston connectors	45	1.77	32	1.26
On printed circuit board	30	1.18	30	1.18


Detail of Lug Recess



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3) Ø22.5 mm recommended (Ø22.3 $_0^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 in. $_0^{+0.016}$)


Technical Illustration

Dimensions



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB5



Offer Marketing Illustration

Product benefits / Features



Image of product / Alternate images

Alternative









13





Image of product in real life situation

