

selector switch \emptyset 30 - 2 positions - maintained - LED

9001K11J35LLL

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony 9001K	
Product or Component Type	Illuminated selector switch	
Device short name	9001K	
Type of operator	maintained	
Operator profile	Blue standard knob	

Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.2 in (30 mm)	
Net Weight	0.540 lb(US) (0.245 kg)	
Shape of signaling unit head	Round	
Operator position information	2 positions	
Contacts type and composition	Without contact block	
Mechanical durability	500000 cycles	
Light block supply	Direct	
Light source	LED	
Bulb base	BA 9s	
[Us] rated supply voltage	2428 V AC/DC	
Device presentation	Basic element	

Environment

Protective treatment	TC	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Electrical shock protection class	Class II IEC 61140	
IP degree of protection	IP66 IEC 60529	
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Standards	IEC 60947-5-4	
	UL 508	
	IEC 60947-1	
	JIS C 852	
	JIS C 4520	
	IEC 60947-5-1	
	CSA C22.2 No 14	
Product Certifications	NEMA	
	UL 508	
Vibration resistance	7 gn (f= 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	50 gn IEC 60068-2-27	

Ordering and shipping details

	· · · · ·
Category	US10CS121426
Discount Schedule	0CS1
GTIN	785901906414
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.81 in (4.6 cm)
Package 1 Width	2.28 in (5.8 cm)
Package 1 Length	3.70 in (9.4 cm)
Package 1 Weight	5.8 oz (163.3 g)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.

Use Again

○ Repack and remanufacture		
Take-back	No	