# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# Thermal pad, SE Relays solid state relay accessory

SSR-TP-1

Product availability: Non-Stock - Not normally stocked in distribution facility

# Main

Range of Product	Legacy
Accessory / Separate Part Type	Protective sheet
Quantity per Set	10 pieces

# Complementary

Product compatibility	1 solid state relay SSR	
Width	1.72 in (43.63 mm)	
Depth	2.2 in (56.3 mm)	

# Ordering and shipping details

Category	US10CP221127
Discount Schedule	0CP2
GTIN	3606480282959
Returnability	No
Country of origin	CN

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.04 in (0.1 cm)	
Package 1 Width	1.72 in (4.363 cm)	
Package 1 Length	2.22 in (5.63 cm)	
Package 1 Weight	0.04 oz (1.1 g)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### **Use Better**


Materials and Substances	
Packaging without single use plastic	Yes
China RoHS Regulation	China RoHS declaration
California proposition 65	"WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"

### **Use Again**

♡ Repack and remanufacture	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	No

**Dimensions Drawings** 

# **Approximate Dimensions**



### INSTALLATION:

- RELEASE LINER ON ONE SIDE OF THE THERMAL PAD, PLACE UNDERNEATH CLASS 6 SOLID STATE RELAY.
- 2. RELEASE LINER ON OTHER SIDE OF THERMAL PAD AND PLACE RELAY AND PAD ONTO HEAT SINK OR PANEL.