

# Auxiliary contacts, TeSys GS, 1 NC, early break, front mounting, for GS2 with front/side handle

GS1AM101

Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

Range of Product	TeSys	
Device short name	GS1AM	
Product or Component Type	Auxiliary contact	
Contact application	O, I and test position signalling	
Range compatibility	TeSys TeSys GS fuse-switch disconnector FuPact FuPacT GS fuse-switch disconnector	
Contacts type and composition	1 NC	
Contact operation	Early-break	
[Ith] conventional free air thermal current	10 A (at 104 °F (40 °C))	
[le] rated operational current	6 A 120 V AC-15 3 A 240 V AC-15	
	1.8 A 400 V AC-15	
	1.5 A 480 V AC-15	
	2.8 A 24 V DC-13	
	1.4 A 48 V DC-13	
	0.55 A 125 V DC-13	
	0.27 A 250 V DC-13	
	0.15 A 400 V DC-13	

## Complementary

Mechanical durability	5 Mcycles
Electrical durability	1 Mcycles AC-15
switch rated current	30 A
	32 A
	50 A
	60 A
	63 A
	100 A
	125 A
	160 A
	200 A
	250 A
	315 A
	400 A
	600 A
	630 A
	800 A
	1250 A
Fuse type	NFC
	DIN
	BS
	CC
	J
Type of operating handle	External frontal
	External right side

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

External left side

Mounting Location	Front face	
Net Weight	0.033 lb(US) (0.015 kg)	

# Ordering and shipping details

Category	US10I1122640
Discount Schedule	0111
GTIN	3389110181784
Returnability	No
Country of origin	FR

# **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.59 in (1.5 cm)
Package 1 Width	2.36 in (6 cm)
Package 1 Length	3.15 in (8 cm)
Package 1 Weight	0.5 oz (13 g)
Unit Type of Package 2	S01
Number of Units in Package 2	10
Package 2 Height	5.91 in (15 cm)
Package 2 Width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	11.005 oz (312 g)

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

#### **Use Better**

<b>⊗</b> Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

### **Use Again**

○ Repack and remanufacture		
Take-back	No	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	