



Contactor, Definite Purpose, auxiliary contact, 3A at 120VAC, 1 NO contact, for 20A to 90A DPA contactors

9999D10

Product availability: Stock - Normally stocked in distribution facility

Main

Product Range	DPA	
Component type	Auxiliary Contact Module	
Used with	contactor	

Complementary

Auxiliary contact composition	1 NO	
Rated breaking capacity	3 A 120 V AC inductive control circuit UL 508	
	1.5 A 240 V AC inductive control circuit UL 508	
	0.75 A 480 V AC inductive control circuit UL 508	
	0.6 A 600 V AC inductive control circuit UL 508	
	5 A <= 600 V AC resistive control circuit UL 508	

Environment

Product Certifications	CSA
	UL Recognized

Ordering and shipping details

Category	US1CP1B21762
Discount Schedule	CP1B
GTIN	785901080862
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.70 in (1.778 cm)
Package 1 Width	1.70 in (4.318 cm)
Package 1 Length	2.80 in (7.112 cm)
Package 1 Weight	1.120 oz (31.751 g)

Contractual warranty

Warranty 18 months

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions

Use Again

○ Repack and remanufacture		
Take-back	No	