



PDU Power Cord, C13 to C14 - 10A, 250V, 18 AWG, 6 ft. (1.83 m), Orange

MODEL NUMBER: P004-006-AOR











Computer power extension cord connects 2 devices with C13/C14 power connectors or extends your existing power connection by 6 ft.

Features

C14-to-C13 Power Cable Connects Computers, Printers, Servers and Other EquipmentThis IEC-320-C14 to IEC-320-C13 cable is designed for small data center, office workstation and other lower-amp applications. This C14 male to C13 female cord can be used to power a computer, server or monitor; attach a server or drive to a UPS system or PDU; or extend an existing connection up to 6-ft. (1.83 m). The 6-ft. (1.83 m) length allows you flexibility in placing equipment with respect to the power outlet.

Color-Coded to Avoid Misidentification That Can Cause Costly DowntimeThis computer power extension cord features an orange SJT jacket and fully molded orange ends. The color-coding allows easy, fast identification in a crowded rack or workstation and helps prevent the cable from becoming inadvertently disconnected.

Highlights

- Recommended for powering computers, printers and other essential peripherals
- Adds 6-ft. (1.83 m) to your existing connection to provide more flexibility in placing devices
- C13-to-C14 PDU-style extension cord is ideal replacement for worn-out or missing cable
- Color-coded orange for fast, easy identification in a crowded rack or workstation

Applications

- Connect devices like computers, servers and monitors to a PDU up to 6-ft. (1.83 m) away in your data center
- Extend an existing power connection up to 6-ft. (1.83 m) to more easily place a device or reach a power source away from your workstation
- Provide a high-quality replacement for a worn-out or missing power cord

Package Includes

 P004-006-AOR C14 Male to C13 Female Power Cable, 6-ft. (1.83 m), Orange

Specifications

| OVERVIEW | | |
|-----------------------------|---|--|
| UPC Code | 037332199386 | |
| Device Compatibility | Computer; Monitor/HDTV; Printer; Server; UPS; PDU | |
| Country/Region | Global | |
| | | |
| INPUT | | |
| Maximum Input Amps | 10 | |
| Voltage Compatibility (VAC) | 100-250 | |
| | | |
| CONNECTIONS | | |
| Side A - Connector 1 | IEC-320-C14 | |





| Side B - Connector 1 | IEC-320-C13 | |
|---------------------------------|-------------------------------------|--|
| PLIVOICAL | | |
| PHYSICAL | | |
| Plug Color | Orange | |
| Cable Jacket Color | Orange | |
| Cable Jacket Material | PVC | |
| Cable Jacket Rating | FT2 | |
| Power Cord Jacket Type | SJT | |
| Cable Outer Diameter (OD) | 7.7mm | |
| Number of Conductors | 3 | |
| Wire Gauge (AWG) | 18 | |
| Wire Gauge (OD - mm²) | 0.82 | |
| Cable Length (ft.) | 6 | |
| Cable Length (m) | 1.83 | |
| Cable Length (cm) | 182.88 | |
| Shipping Dimensions (hwd / in.) | 9.90 x 7.00 x 0.50 | |
| Shipping Dimensions (hwd / cm) | 25.15 x 17.78 x 1.27 | |
| Shipping Weight (lbs.) | 0.51 | |
| Shipping Weight (kg) | 0.23 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Storage Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Operating Humidity Range | 20% to 80% RH | |
| Storage Humidity Range | 20% to 80% RH | |
| | | |
| FEATURES & SPECIFICATIONS | | |
| Antibacterial | No | |
| Angled Plug | No | |
| High Voltage | Yes | |
| Locking Plug | No | |
| Coiled Power Cord | No | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | CSA (Canada); cUL Listed; UL Listed | |
| Product Compliance | RoHS; REACH | |
| WARRANTY & SUPPORT | | |





| Product Warranty Period (Worldwide) | Lifetime limited warranty |
|-------------------------------------|---------------------------|
|-------------------------------------|---------------------------|

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.