



# Safe-IT USB 2.0 A to USB Mini-B Antibacterial Cable (M/M), White, 3 ft. (0.91 m)

MODEL NUMBER: U030AB-003-WH











USB cable with antibacterial properties connects mobile devices to your computer while helping to protect you from harmful bacteria.

#### **Features**

### Durable USB-A to USB Mini-B Cable Transfers Important Data at USB 2.0 Speeds

This USB cable (M/M) connects a digital camera, MP3 player, smartphone or other Mini-B peripheral with a 5-pin port to the USB-A port on your computer or laptop. It transfers data at USB 2.0 speeds up to 480 Mbps for use with low-speed and high-speed devices, including multimedia applications. The cable is also backward compatible with earlier USB generations.

#### **Provides Extra Protection Against Certain Bacteria**

The molded connectors and PVC jacket are constructed using an antibacterial material that is effective in inhibiting the growth of Escherichia coli (E. coli) and Staphylococcus aureus (staph). This added protection makes this cable an ideal solution for medical facilities, schools, businesses, restaurants/kitchens and anywhere else that needs extra protection against bacteria.

# **Premium Construction for Superior Performance**

Manufactured with twisted 28 AWG data lines and 28 AWG power lines, the U030AB-003-WH also features molded gold-plated connectors and contacts that provide maximum conductivity and minimum data loss to guarantee a clear transmission free of interference. Integral strain relief gives the cable extra flexibility, reduces stress and helps the cable move freely without cracking or breaking loose from the connector.

# White Jacket Helps Avoid Misidentification That Can Cause Costly Downtime

The cable has a white PVC jacket, which is easy to identify quickly in a crowded computer or hub and helps prevent the cable from becoming accidentally disconnected.

# **Specifications**

OVERVIEW	
UPC Code	037332260666
Technology	USB 2.0 (High Speed)

## **Highlights**

- Supports USB 2.0 speeds up to 480 Mbps to ensure efficient data transfers
- Made with antibacterial material proven effective in inhibiting the growth of E. coli and staph
- Foil and braid shielding protects against EMI/RFI noise that can distort or destroy data
- Gold-plated connectors and contacts for maximum conductivity and minimum data loss
- White jacket permits fast, easy identification in a crowded hub or computer

#### **Applications**

- Connect a computer or laptop and a USB Mini-B peripheral in a home or office network
- Provide extra protection against bacteria to give cable installers and IT personnel peace of mind during installation

# Package Includes

U030AB-003-WH USB-A to USB Mini-B Antibacterial Cable (M/M), White, 3-ft. (0.91 m)





Cable Type	Passive	
CONNECTIONS		
Side A - Connector 1	USB A (MALE)	
Side B - Connector 1	USB MINI-B 5-PIN (MALE)	
Connector Plating	Gold	
Contact Plating	Gold	
Connector Style	Straight	
PHYSICAL		
Material of Construction	PVC	
Cable Jacket Color	White	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	3.8MM	
Wire Gauge (AWG)	28/28	
Cable Length (ft.)	6	
Cable Length (m)	1.83	
Cable Length (in.)	36	
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50	
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27	
Shipping Weight (lbs.)	0.06	
Shipping Weight (kg)	0.03	
Unit Packaging Type	Polybag	
ENVIRONMENTAL		
Operating Temperature Range	14° to 122°F (-10° to 50°C)	
Storage Temperature Range	5° to 140°F (-15° to 60°C)	
Operating Humidity Range	0% to 90% RH, Non-Condensing	
Storage Humidity Range	0% to 90% RH, Non-Condensing	
FEATURES & SPECIFICATIONS		
Antimicrobial	No	
USB Specification	USB 2.0 (up to 480 Mbps)	
Antibacterial	Yes	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH	
· ·		





WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.