



Quality Products. Service Excellence.

Horizontal Ring Cable Manager *RB-HRM Series*

TOP SELLER



Features

- Constructed in 16-gauge steel.
- Flanged at front for added strength.
- Designed to fit standard 19" rails.
- Rings extend 3.69 inches from the panel front.
- Includes four (4) cable pass-through cutouts.
- Designed to mount two (2) units back-to-back.
- Requires mounting hardware.
- Finished in textured RAL9005 black powder paint finish.
- TAA-compliant for federal GSA schedule purchases within the USA.
- RoHS and REACH compliant.
- Manufactured in North America.

Part of the Rack Basics® line of value rack solutions.

Accessories

- Hardware for Rack Mounting Solutions
- Hook and Loop Convenience Roll



A HAMMOND BRAND



Part No.	Overall Dinmensions			Usable Mounting Dimensions	
	Height	Width	Depth	Rack Units	Height
RB-HRM1	1.72	19.00	3.69	1U	1.75
RB-HRM2	3.22	19.00	3.69	2U	3.50

Estimated Cable Fill Capacities

Rack Units	Description	Opening Quantity	Recommended Cable Fill (50% Fill Ratio)			Maximum Cable Fill (100% Fill Ratio)		
			Cat 5e	Cat 6	Cat 6a	Cat 5e	Cat 6	Cat 6a
1U	Channel Opening	1	50	32	22	100	64	45
	Rear Pass Through	4	16	10	7	32	20	14
2U	Channel Opening	1	102	65	45	204	130	91
	Rear Pass Through	4	25	16	11	49	32	22

Data subject to change without notice

