G4TAATO-H005WN-LS00

ODU AMC® Series T



Square flange receptacle for rear or front panel mounting, MIL-DTL-38999

General information

Cable Diameter

Part number	G4TAATO-H005WN-LS00	
Termination	Solder	
Size	12 (STD 38999)	
Locking principle	Break-Away , Push-Pull , Screwlocking	
Coding	A (light brown)	





Illustrations may differ from original product. Dimensions, unless otherwise specified, in mm.





5 – 14.6 mm





The pin layout corresponds to the view on the termination area

Contact insert description

Number of contacts	5
Contact type	Sockets
Contact diameter	1.6 mm
Insulator material	PEEK
Wire cross section	AWG 16 – 20
Termination	Solder

Technical information

Nominal current single contact	13 A	IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003)
Test voltage	1.8 kV AC	EIA-364-20F:2019-02

All shown connectors are rated to a safety extra low voltage (SELV) of less than 50 V AC / 75 V DC, according to IEC 61140:2016 (VDE 0140-1:2016) Protection against electric shock - Common aspects for installation and equipment. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. In this context, lower voltage ratings may be valid. Warning: Danger to life for operating voltages above 50 V AC / 120 V DC!

Mechanical and environmental data

Degree of protection*	IP6K8/IP6K9K	
Operating temperature	-65 °C − 175 °C	
Mating cycles	500	
*mated condition		

Material and surface treatments

Contact

Cu-alloy with gold finish

All shown connectors are defined without breaking capacity (COC) according to IEC 61984:2008 (VDE 0627:2009).

The contact arrangement of an ODU data transmission connector differs from a standard data transmission connector due to the robust ODU specific design. However, the ODU design meets the electrical specifications that are derived from the respective standard data transmission protocol.

ODU MEDI-SNAP® and MINI-SNAP® are UL-approved (E110586).

ODU reserves the right to make changes based on the current state of knowledge without prior notice without being obliged to provide replacement deliveries or refinements of older designs.