



Mini-Circuits

MMIC SURFACE MOUNT

Monolithic Amplifier

GALI-51+

50Ω DC to 4 GHz

FEATURES

- Frequency Range, DC to 4 GHz
- InGaP HBT Microwave Amplifier
- Miniature SOT-89 Package
- Internally Matched to 50Ω
- Output Power, +18.0 dBm Typ.
- Excellent Package for Heat Dissipation, Exposed Metal Bottom
- Low Thermal Resistance for High Reliability
- Aqueous Washable
- Protected By US Patent 6,943,629



Generic photo used for illustration purposes only

CASE STYLE: DF782

+RoHS Compliant

The +Suffix identifies RoHS Compliance.
See our website for methodologies and qualifications



APPLICATIONS

- Cellular
- PCS
- Communication Receivers & Transmitters

PRODUCT OVERVIEW

Gali-51+ (RoHS compliant) is a wideband amplifier offering high dynamic range. It has repeatable performance from lot to lot, and is enclosed in a SOT-89 package. It uses patented Transient Protected Darlington configuration and is fabricated using InGaP HBT technology. Expected MTTF is 7,000 years at +85°C case temperature. Gali-51+ is designed to be rugged for ESD and supply switch-on transients.

SIMPLIFIED SCHEMATIC AND PIN DESCRIPTION



Function	Pin Number	Description
RF-IN	1	RF input pin. This pin requires the use of an external DC blocking capacitor chosen for the frequency of operation.
RF-OUT and DC-IN	3	RF output and bias pin. DC voltage is present on this pin; therefore a DC blocking capacitor is necessary for proper operation. An RF choke is needed to feed DC bias without loss of RF signal due to the bias connection, as shown in "Recommended Application Circuit".
GND	2,4	Connections to ground. Use via holes as shown in "Suggested Layout for PCB Design" to reduce ground path inductance for best performance.

Mini-Circuits



MMIC SURFACE MOUNT

Monolithic Amplifier

GALI-51+

50Ω DC to 4 GHz

ELECTRICAL SPECIFICATIONS AT +25°C AND 65 mA UNLESS NOTED OTHERWISE

Parameter	Conditions (GHz)	Min.	Typ.	Max.	Units
Frequency Range ¹		DC		4	GHz
Gain	0.1	14	18.1		dB
	1		17.5		
	2		16.1		
	3		14.7		
	4		13.7		
	5		13.4		
Input Return Loss	DC - 3		17.5		dB
	3 - 4		21		
Output Return Loss	DC - 3		14		dB
	3 - 4		11.5		
Output Power @ 1 dB Compression	1	+16.5	+18.0		dBm
Output IP3	1		+35		dBm
Noise Figure	1		3.5		dB
Recommended Device Operating Current			65		mA
Device Operating Voltage		+4.2	+4.5	+5.5	V
Device Voltage Variation vs. Temperature at 65 mA			-3.2		mV/°C
Device Voltage Variation vs. Current at +25°C			5.8		mV/mA
Thermal Resistance, Junction-to-Case ²			78		°C/W

1. Guaranteed specification DC-4 GHz. Low frequency cut off determined by external coupling capacitors.

2. Case is defined as ground leads.

ABSOLUTE MAXIMUM RATINGS

Parameter	Ratings
Operating Temperature ³	-45°C to +85°C
Storage Temperature	-65°C to +150°C
Operating Current	85 mA
Input Power	+13 dBm

3. Based on typical case temperature rise +5°C above ambient.

Permanent damage may occur if any of these limits are exceeded. These ratings are not intended for continuous normal operation.





Monolithic Amplifier

GALI-51+

50Ω DC to 4 GHz

The diagram shows a common-emitter amplifier circuit. The input signal IN is connected to the base of the transistor through a coupling capacitor C_{block} (labeled 1). The base is biased by a voltage divider consisting of a resistor R_{bias} (labeled "Required") connected to V_{cc} and a bypass capacitor C_{bypass} connected to ground. The emitter is connected to ground through a resistor R_{E} (labeled 4) and a bypass capacitor C_{bypass} . The collector is connected to V_{cc} through a resistor R_C (labeled 3) and a radio-frequency choke (RFC) (labeled "Optional"). The output signal OUT is taken from the collector through a coupling capacitor C_{block} (labeled 2). The DC voltage at the collector is labeled V_d .

R BIAS	
Vcc	"1%" Res. Values (Ohms) for Optimum Biasing
7	40.2
8	53.6
9	68.1
10	82.5
11	97.6
12	113
13	127
14	143
15	158
16	174
17	191
18	205
19	221
20	237

A diagram of a 51-bit register. It is represented as a rectangle with a double border. Inside the rectangle, the number "51" is written in a large, bold, black font. Above the rectangle, there is a semi-circular input port labeled with the number "4" in blue. Below the rectangle, there are three vertical output ports labeled with the numbers "1", "2", and "3" in blue.



MMIC SURFACE MOUNT

Monolithic Amplifier

GALI-51+

50Ω DC to 4 GHz

ADDITIONAL DETAILED TECHNICAL INFORMATION IS AVAILABLE ON OUR DASHBOARD. [CLICK HERE](#)

Performance Data & Graphs	Data Table
	Swept Graphs
	S-Parameter (S2P Files) Data Set (.zip file)
Case Style	DF782 Plastic package, Lead Finish: Matte-tin
Tape & Reel Standard Quantities Available on Reel	F55 7" Reels with 20, 50, 100, 200, 500 or 1K devices
Suggested Layout for PCB Design	PL019
Evaluation Board	TB-409-51+
Environmental Ratings	ENV08T2

ESD RATING

Human Body Model (HBM): Class 1B (500 V to < 1000 V) in accordance with ANSI/ESD STM 5.1 - 2001


Machine Model (MM): Class M1 (< 100 V) in accordance with ESD STM 5.2 - 1999

MSL RATING

Moisture Sensitivity: MSL1 in accordance with IPC/JEDECJ-STD-020C

No.	Test Required	Condition	Standard	Quantity
1	Visual Inspection	Low Power Microscope Magnification 40x	MIP-IN-0003 (MCT spec)	45 units
2	Electrical Test	Room Temperature	SCD (MCL spec)	45 units
3	SAM Analysis	Less than 10% growth in term of delamination	J-Std-020C (Jedec Standard)	45 units
4	Moisture Sensitivity Level 1	Bake at 125°C for 24 hours Soak at 85°C/85%RH for 168 hours Reflow 3 cycles at 260°C peak	J-Std-020C (Jedec Standard)	45 units

MSL TEST FLOW CHART



NOTES

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/terms/viewterm.html

