

1

2

3

RUBBER PART GENERAL TOLERANCE				
PART DIM.	1	2	③	
0 TO 3	± 0.2	± 0.3	± 0.4	
3 TO 6	± 0.2	± 0.4	± 0.5	
6 TO 10	± 0.3	± 0.5	± 0.6	
10 TO 18	± 0.3	± 0.6	± 0.8	
18 TO 30	± 0.4	± 0.8	± 1.0	
30 TO 50	± 0.5	± 1.0	± 1.5	
50 TO 80	± 0.6	± 1.2	± 2.0	
80 TO 120	± 0.7	± 1.4	± 2.5	
120 TO 180	± 0.8	± 1.6	± 3.0	
180 TO 250	± 1.0	± 2.0	± 4.0	
250 TO 315	± 1.2	± 2.5	± 5.0	
315 TO 400	± 1.5	± 3.0	± 6.0	
400 TO 500	± 1.8	± 3.5	± 7.0	
500 OVER	± 0.4%	± 0.8%	± 1.5%	

注記

1. 色：濃灰色トスル。

2. 材料：含油NBR

NOTES

1. COLOR : DARK GRAY

2. MATL&SPEC : SELF-LUBRICATING. NBR

A

SEC. A-A

ISSUE MARK

								CUSTOMER				MATL. SPEC.				SEE NOTES		TREAT. & FIN.	
								CUSTOMER PART NO.				CUSTOMER DWG NO.							
	90.10.01	NEW			C90-M079	T. S	OFFICE				STDLIB NO.				NAME 187 PLUGGING RUBBER				
LET	DATE	REVISION RECORD			NO.	CHKD	VENDOR								STOPPER				
GENERAL TOLERANCE							VENDOR NO.												
	10MAX	50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO. 7157-8763					
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30°	0.1	R	NEW	90.10.01	mm	10/1	3						
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30°	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	DWG NO. 7157-8763:R		TRIAL PART NO.				
C	±0.3	±0.5	±0.8	±1.4	±2	±30°	0.15				M. TSUJI	T. MAKITA							
SPECIFIED RUBBER PART GENERAL TOLERANCE 3						WEIGHT						YAZAKI CORPORATION							
						g		90.11.02	90.11.02	90.10.31	88.08.20	90.10.01							

1

2

3