

GENERAL TOLERANCE											
	10 MAX.	50 MAX.	100 MAX.	250 MAX.	500 MAX.	R5 MAX.	R10 MAX.	R20 MAX.	R20 OVR.	ANGLE	ECCENT
A	+0.15	±0.2	±0.3	±0.5	±0.75					+3°	0.1
B	+0.2	±0.3	±0.55	±0.95	±1.4	±0.2	±0.3	±0.5	±2.5	+3°	0.1
C	±0.3	±0.5	±0.8	±1.4	±2					+3°	0.15

TABLE 1

[illegible]

TABLE 2

ASSEMBLY PART NO.	NOL.	PART NO.	PART NAME	MATERIAL	COLOR
SEE TABLE 1	①	7188-3341-30	0 64 II 22P J/C HOUSING MALE	PBT	BLACK
	②	7172-0965-30	0 64 II 22P J/C REAR HOLDER	PBT	BLACK
	③~⑤	7117-5520-02 ETC.	0 64 II 22P J/C 3P TERMINAL MALE ETC.	BRASS	-

[illegible]

5

[illegible]

A

Technical drawing showing the front view of a rectangular metal plate. The dimensions are as follows:

- Overall width: 15.90
- Overall height: 22.00
- Inner width (between mounting holes): 13.20
- Inner height (between mounting holes): 8.80
- Distance from top edge to top mounting hole center: 4.40
- Distance from bottom edge to bottom mounting hole center: 2.00
- Distance from left edge to left mounting hole center: 3.00
- Distance from right edge to right mounting hole center: 2.00

A section line A-A is indicated, passing through the center of the plate.

SEC. A-A

[illegible]

LET	DATE	2014/10/01	NEW	C14-2586	B A
			REVISION RECORD	NO.	CHKD