



Features

- Designed to UL 248-19 (gPV) photovoltaic fuse standard
- 1500 VDC and 4-30 A ratings available
- Up to 50 kA interrupting rating
- Available in ferrule and crimp cap options
- RoHS compliant* and halogen free**



PF-PVC150R Series – Photovoltaic (gPV) Power Fuses

Clearing Time Characteristics for Series

% of Current Rating	Clearing Time at 25 °C	
	Minimum	Maximum
100 %	4 hours	—
135 %	—	60 minutes
200 %	—	4 minutes

Additional Information

Click these links for more information:



[PRODUCT
SELECTOR](#)



[TECHNICAL
LIBRARY](#)



[INVENTORY](#)



[SAMPLES](#)



[CONTACT
US](#)

Electrical Characteristics

Model	Rated Current (A)	Nominal Resistance (mΩ)***	Rated Voltage	Interrupting Rating	Nominal I²t (A²s)****	Watts Loss (W)		 LISTED
						@ 70 % In	@ 100 % In	
PF-PVC150R4C1	4	106.7	1500 VDC	50 kA @ 1500 VDC	56	1.7	2.8	E526252
PF-PVC150R4C2								
PF-PVC150R5C1	5	68.1			70	1.7	2.8	
PF-PVC150R5C2								
PF-PVC150R6C1	6	43.3			86	1.8	2.9	
PF-PVC150R6C2								
PF-PVC150R8C1	8	30.0			192	1.8	3.1	
PF-PVC150R8C2								
PF-PVC150R10C1	10	25.3			320	2.0	3.3	
PF-PVC150R10C2								
PF-PVC150R12C1	12	19.0			576	2.1	3.5	
PF-PVC150R12C2								
PF-PVC150R15C1	15	16.1			675	3.1	5.6	
PF-PVC150R15C2								
PF-PVC150R16C1	16	12.5			768	3.3	6.5	
PF-PVC150R16C2								
PF-PVC150R20C1	20	10.3			880	4.4	6.8	
PF-PVC150R20C2								
PF-PVC150R25C1	25	7.27			937	4.9	8.1	
PF-PVC150R25C2								
PF-PVC150R30C1	30	4.80			3060	5.0	10.0	
PF-PVC150R30C2								

*** Resistance value was measured with less than 10 % of rated current at 25 °C.

**** Nominal I²t value is measured at 1000 % of rating current.

* RoHS Directive 2015/863, Mar 31, 2015 and Annex.

** Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.

"SinglFuse" is a trademark of Bourns, Inc. Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.




CALIFORNIA WARNING Can expose you to lead, a carcinogen and reproductive toxicant. See www.P65Warnings.ca.gov

PF-PVC150R Series – Photovoltaic (gPV) Power Fuses


BOURNS®

Product Dimensions


Ferrule / C1 Type



Crimp Cap / C2 Type



Average Pre-Arcing Time vs. Current Curves



How to Order

PF - PVC 150R 10 C1

POW'rFuse™ _____
 Product Designator _____
 Series Name _____
 Rated Voltage _____
 150R = 1500 VDC
 Rated Current _____
 4 - 30 = 4A - 30 A
 Mounting Type _____
 C1 = Ferrule, Type 1
 C2 = Crimp Cap, Type 2

Packaging

Model	Quantity	
	Inner Box	Outer Box
PF-PVC150R-C1	20 pcs.	700 pcs.
PF-PVC150R-C2	35 pcs.	420 pcs.

Specifications are subject to change without notice.


Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

PF-PVC150R Series – Photovoltaic (gPV) Power Fuses

BOURNS®

Current Rating Thermal Derating Curve



Environmental Characteristics

Operating Temperature	-40 °C to +90 °C
-----------------------	------------------

Typical Part Marking

Rating Current (A)	Note	Style	Marking
4	4	Label stuck to tube	 PF-PVC150R (Note) A 1500VDC gPV IR 50kA
5	5		
6	6		
8	8		
10	10		
12	12		
15	15		
16	16		
20	20		
25	25		
30	30		

BOURNS®

Americas: Tel: +1 951-781-5500 • Email: americus@bourns.com

Mexico: Tel: +52-614-478-0400 • Email: mexicus@bourns.com

Asia: Tel: +886-2-2562-4117 • Email: asiacus@bourns.com

EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com

www.bourns.com

REV. 08/25

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <http://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <http://www.bourns.com/docs/Legal/disclaimer.pdf>