

M12 panel feedtrough/PCB straight A-cod.



| Part number | 21 03 321 1510 |
|--------------------|---|
| Specification | M12 panel feedtrough/PCB straight Acod. |
| HARTING eCatalogue | https://harting.com/21033211510 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|---------------|----------------------------|
| Series | Circular connectors M12 |
| Element | PCB adapter |
| Specification | Straight for rear mounting |

Version

| Termination method | Reflow soldering termination (THR) |
|--------------------|------------------------------------|
| Gender | Male |
| Shielding | Shielded |
| Number of contacts | 5 |
| Coding | A-coding |
| Locking type | Screw locking |

Technical characteristics

| Rated current | 4 A |
|-----------------------|--------------------|
| Rated voltage | 60 V |
| Rated impulse voltage | 1.5 kV |
| Pollution degree | 3 |
| Overvoltage category | III |
| Insulation resistance | >10 ⁸ Ω |
| Contact resistance | ≤10 mΩ |
| Tightening torque | 2 Nm Lock nut |



Technical characteristics

| Limiting temperature | -40 +85 °C |
|--|---------------|
| Mating cycles | ≥100 |
| Degree of protection acc. to IEC 60529 | IP20 |
| Isolation group | I (600 ≤ CTI) |

Material properties

| Material (insert) | Polyamide (PA) |
|---|--|
| Material (contacts) | Copper alloy |
| Surface (contacts) | Au over Ni Mating side |
| Material (hood/housing) | Zinc die-cast |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 0d7d3693-d625-47ab-934a-d241bf72c86e |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) + A1 (2023-10) |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

Commercial data

| Packaging size | 10 |
|--------------------------------|----------|
| Net weight | 19.6 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |

Product data sheet 21 03 321 1510 M12 panel feedtrough/PCB straight A-cod.



Commercial data

| GTIN | 5713140137684 |
|-------------|--|
| eCl@ss | 27460201 PCB connector (board connector) |
| ETIM | EC002637 |
| UNSPSC 24.0 | 39121415 |