

## M12-PFT-CRIMP-8P-YCOD-F-SHLD-0.3



Image is for illustration purposes only. Please refer to product description.

Part number	21 43 369 2801
Specification	M12-PFT-CRIMP-8P-YCOD-F-SHLD-0.3
HARTING eCatalogue	<a href="https://harting.com/21433692801">https://harting.com/21433692801</a>

### Identification

Category	Connectors
Series	Circular connectors M12
Identification	Data Power
Element	Panel feed through
Specification	With conductors for rear mounting

### Version

Cable length	0.3 m
Gender	Female
Shielding	Shielded
Number of contacts	8
Number of data contacts	4
Number of power contacts	4
Coding	Y-coding
Locking type	Screw locking

### Technical characteristics

Conductor cross-section [AWG]	AWG 26 Data AWG 20 Power
Rated voltage	30 V AC/DC
Rated impulse voltage	0.8 kV
Pollution degree	3



**Pushing Performance**  
Since 1945

## Technical characteristics

Rated current (data)	0.5 A
Rated current (power)	6 A
Overvoltage category	III
Insulation resistance	$>10^8 \Omega$
Contact resistance	$\leq 10 \text{ m}\Omega$
Tightening torque	0.6 Nm 2 Nm Lock nut
Limiting temperature	-25 ... +85 °C
Mating cycles	$\geq 100$
Degree of protection acc. to IEC 60529	IP67
Isolation group	I ( $600 \leq \text{CTI}$ )

## Material properties

Material (insert)	Polyamide (PA)
Material (contacts)	Brass
Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast

## Specifications and approvals

Specifications	IEC 61076-2-113
PROFINET	Yes

## Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85444290
GTIN	5713140227859
eCl@ss	27440103 Sensor-actuator connector chassis (sensor technology actuator)
UNSPSC 24.0	39121413