



Pushing Performance
Since 1945

Carrier_BT494030_SOT23-6_h LCP




Image is for illustration purposes only. Please refer to product description.

Part number	78 01 030 0003
Specification	Carrier_BT494030_SOT23-6_h LCP
HARTING eCatalogue	https://harting.com/78010300003

Identification

Category	Surface Mount Device
Series	3D-MID
Element	Carrier for electronic components
Specification	Interconnection
Features	Other materials or trace layouts on request!

Version

Fixing	PCB assembly (SMD)
Pack contents	Tape & reel 3400 pieces on reel Lower quantities available on request!

Technical characteristics

Operating temperature	-40 ... +125 °C
Storage temperature	-40 ... +125 °C

Material properties

Material	Liquid crystal polymer (LCP)
Surface (contacts)	Au ($\geq 0.05 \mu\text{m}$) over Ni ($\geq 4 \mu\text{m}$) over Cu (5...11 μm)
Length	4.9 mm
Width	4 mm
Height	3 mm
RoHS	compliant
ELV status	compliant



Pushing Performance
Since 1945

Material properties

China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained


Commercial data

Packaging size	1
Net weight	0.315 g
Country of origin	Switzerland
European customs tariff number	85340090
GTIN	5713140277403
eCl@ss	27469090 PCB connection technology (other, unspecified)
ETIM	EC002637
UNSPSC 24.0	39121415


Other materials or trace layouts on request!




Drawing (dimensions in mm)




Drawing (dimensions in mm)




COMPONENT PADS LAYOUT
SOT-23-6



SOLDERING PADS




CARRIER PATTERN LAYOUT




RECOMMENDED PCB PATTERN LAYOUT

Soldering instructions



PB-free soldering profile (J-STD-020C)






Pushing Performance
Since 1945


Tape layout & packaging

BT494030

MATERIAL
PS Conductive Black surface resistance $10^{-3}\Omega$ - $10^{-6}\Omega$

DIMENSIONS	
W	= 16 mm
P	= 8 mm
T	= 0,4 mm
Ao	= 3,3 mm
Bo	= 4,3 mm
Ko	= 5,2 mm
TRAILER	20 cvt
FILL IN	1700 pcs
LEADER	50 cvt



PACKING					
		REEL		BOX	PALLET
LENGTH		42 m		630m	7560 m
CAVITIES		5250 cvt		78750 cvt	945000 cvt
PARTS		3400 pcs[2x1700]		51000 pcs	612000 pcs
WEIGHT		0,63kg		10,71 kg	143,5 kg
QTY		Single Reel		15 reels/box	12 boxes/pallet
DIMENSION		560/76 x 16 cardboard		39 x 58 x 58 [cm]	80 x 120 x 190 [cm]
				