

1594269

https://www.phoenixcontact.com/us/products/1594269

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: RC, straight, shielded: no, Screw locking mechanism, No. of pos.: 7, Direction of rotation: Standard, contact connection type: Pin, Solder cup, coding: N. This product is in the process of being discontinued. This product must no longer be considered for new projects. Please contact your sales representative for alternatives.

### Commercial data

Item number	1594269
Packing unit	20 pc
Minimum order quantity	1 pc
Sales key	AB31
Product key	ABRAFA
GTIN	4046356200486
Weight per piece (including packing)	85.98 g
Weight per piece (excluding packing)	81.11 g
Customs tariff number	85366990
Country of origin	DE



1594269

https://www.phoenixcontact.com/us/products/1594269

### Technical data

### Product properties

Product type	Circular connector (cable side)
Product type	Circular connector (cable-side)

#### Connector

### Insulating body

Coding	N
Material (Insulating body)	PBT
Material (Contact)	CuZn
Material (Contact surface)	Ni/Au
Insertion/withdrawal cycles	50
Connection method	Solder cup
Contact switching type	Pin
Application	Signal
Number of positions	7
Direction of rotation	Standard
Connection profile	7
Number Contact (Contact group 1)	7
Diameter Contact (Contact group 1)	2 mm
Litz wire cross-section min. Contact (Contact group 1)	0.08 mm <sup>2</sup>
Litz wire cross-section max. Contact (Contact group 1)	2.5 mm²
Rated current Contact (Contact group 1)	20 A (for max. connection cross section)
Rated voltage Contact (Contact group 1)	48 V AC
	74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

#### Housing

g	
Туре	Cable connector housing
Thread type	M23
Design	straight
Type of locking	Screw locking mechanism
Pg screw connection	Pg9
Material (Housing)	GD-Zn
Material (Housing surface)	Ni
Material (Rotating parts)	CuZn
Degree of protection (plugged in)	IP65
	IP67
	IP68




https://www.phoenixcontact.com/us/products/1594269



## Drawings

Schematic diagram




Connector pin assignment



https://www.phoenixcontact.com/us/products/1594269



### Schematic diagram




Connector pin assignment



1594269 https://www.phoenixcontact.com/us/products/1594269



### Schematic diagram



Dimensional drawing



1594269

https://www.phoenixcontact.com/us/products/1594269

### Classifications

#### **ECLASS**

	ECLASS-13.0	27440116	
	ECLASS-15.0	27440116	
ETIM			
	ETIM 9.0	EC002635	
U	NSPSC		
	UNSPSC 21.0	39121400	



1594269

https://www.phoenixcontact.com/us/products/1594269

### Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	e336fa48-6607-4e10-8b59-aad5369e6ce0

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com