

0824414

https://www.phoenixcontact.com/us/products/0824414

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving material, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: adhesive, Number of individual labels: 120, text field height: 9 mm, text field width: 13 mm



Your advantages

- · Labeling service: Phoenix Contact can custom-label all GPE ... markers according to your requirements
- The adhesive foil used ensures good adhesive properties, even on uneven surfaces
- · Two-layer material
- · The label sheet consists of prefabricated, individual self-adhesive labels

Commercial data

Item number	0824414
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8145
GTIN	4046356352840
Weight per piece (including packing)	17.88 g
Weight per piece (excluding packing)	17.88 g
Country of origin	PL



0824414

https://www.phoenixcontact.com/us/products/0824414

Technical data

Product properties

Product type	Labeled device marker
Marking	
Number of individual labels	120
Number of individual labels per row	6
Identification technology	Engraving

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

Adhesive strength	50 μm
Adhesive	Acrylic
Color	white (RAL 9010)
Material	TRANSPLY-ABS
Components	free from silicone and halogen

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

Dimensions

Length 9 mm Material strength 0.80 mm	Width	13 mm
Material strength 0.80 mm	Length	9 mm
iviaterial strength 0.00 mm	Material strength	0.80 mm

Text field



0824414

https://www.phoenixcontact.com/us/products/0824414

	Text field width	13 mm
	Text field height	9 mm
Sta	andards and regulations	
	Wipe resistance	DIN EN 61010-1 (VDE 0411-1)



0824414

https://www.phoenixcontact.com/us/products/0824414

Classifications

	ECLASS-13.0	27281103
E ⁻	ГІМ	
	ETIM 9.0	EC001288
UI	NSPSC	
	UNSPSC 21.0	39131500



0824414

https://www.phoenixcontact.com/us/products/0824414

Environmental product compliance

EU RoHS

EG NOTIC	
Fulfills EU RoHS substance requirements	Yes, No exemptions
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com