

1311006

https://www.phoenixcontact.com/us/products/1311006

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail housing for use in distribution boards in accordance with DIN 43880, for mounting on a DIN rail, with transparent hinged cover, color: black (similar RAL 9005), width: 53.6 mm, height: 89.7 mm, depth: 60.7 mm, incl. 2 PCB terminal blocks, 9-pos., Push-in, for 2.5 mm<sup>2</sup>, nominal current: 24 A, 400 V, PCB surface: 3900 mm<sup>2</sup>

#### Commercial data

Item number	1311006
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AC10
Product key	ACHBAK
GTIN	4063151601386
Weight per piece (including packing)	102.38 g
Weight per piece (excluding packing)	81.03 g
Customs tariff number	85369010
Country of origin	DE



1311006

https://www.phoenixcontact.com/us/products/1311006

#### Set consists of

PTDA 2,5/9-5,0 - PCB terminal block

1725393

https://www.phoenixcontact.com/us/products/1725393



Printed circuit board terminal, nominal current: 24 A, rated voltage (III/2): 400 V, nominal cross section: 2.5 mm², number of potentials: 9, number of rows: 1, number of positions per row: 9, product range: PTDA 2,5/, pitch: 5 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 2, type of packaging: packed in cardboard



1311006

https://www.phoenixcontact.com/us/products/1311006

### Technical data

#### Notes

Assembly note	Please observe the assembly instructions available in the download area.
General	The PCB surface specification is for orientation purposes and is based on a basic PCB. The housing can also accommodate several PCBs.

### Product properties

Product type	Stackable housing set
Housing type	DIN rail housing for use in distribution boards in accordance with DIN 43880
Housing series	BC
Number of positions	18
Max. number of positions	18 (pitch: 5 mm)
Туре	for mounting on a DIN rail, with transparent hinged cover
	incl. 2 PCB terminal blocks, 9-pos., Push-in, for 2.5 $\rm mm^2,$ nominal current: 24 A, 400 V
Ventilation openings present	yes

#### Dimensions

Dimensional drawing	h
Width	53.6 mm
Height	89.7 mm
Depth	60.7 mm
Depth from top edge of DIN rail	54.7 mm
Horizontal pitch	3 Div.
Dimensions	81.54 mm x 49 mm (PCB dimensions)
PCB design	
PCB thickness	1.4 mm 1.8 mm
laterial specifications	
<b>-</b>	

#### M

Color (Lower housing part)	black (RAL 9005)
Color (Upper housing part)	light gray (RAL 7035)
Color (Housing cover)	transparent
Flammability rating according to UL 94	V0



1311006

https://www.phoenixcontact.com/us/products/1311006

Insulating material	Polycarbonat
Housing material	PC
Environmental and real-life conditions	
Ambient conditions	
Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C 70 °C
Ambient temperature (assembly)	-5 °C 100 °C
Relative humidity (storage/transport)	95 %
PCB data	
Number of PCB holders	9
Type of PCB mount	Latching
Total PCB surface	3900 mm²
Thickness of the PCB	1.4 mm 1.8 mm
Mounting	

#### Mounting type

Packaging specifications		
	Type of packaging	packed in cardboard
	Outer packaging type	Carton


DIN rail mounting/panel mounting




1311006

https://www.phoenixcontact.com/us/products/1311006

### Drawings





Schematic figure for illustrating the item dimensions. The figure is not of the desired product. For further details, refer to the product drawings in the "Downloads" tab.



1311006

https://www.phoenixcontact.com/us/products/1311006

### Classifications

ECLASS		
	ECLASS-13.0	27190301
ET	TIM	
	ETIM 9.0	EC001031

UNSPSC

UNSPSC 21.0 31261500



1311006

https://www.phoenixcontact.com/us/products/1311006

### Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com