

1436783

https://www.phoenixcontact.com/us/products/1436783

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 12-position, Pin, straight, M12-SPEEDCON, coding: A, Rear mounting, Pg9, Solder pins, this item is expected to be lead-free from Q2 2026 in accordance with RoHS II without exception 6c (Pb < 0.1%), a lead-free alternative is possible on request in advance

Your advantages

- · Easy PCB assembly: one-piece connectors for wave soldering
- · All standard pin assignments and codings for signal, data, and power transmission with a uniform design-in design
- · SPEEDCON fast locking system reduces cabling times
- · For high transmission reliability: optional shield connection to the housing by means of shield contact

Commercial data

Item number	1436783
Packing unit	20 pc
Minimum order quantity	1 pc
Sales key	AB26
Product key	ABQEGD
GTIN	4046356438797
Weight per piece (including packing)	14.85 g
Weight per piece (excluding packing)	13.356 g
Customs tariff number	85366990
Country of origin	DE



1436783

https://www.phoenixcontact.com/us/products/1436783

Technical data

Notes

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Order information:	Lock nut is included in the scope of delivery

Mounting

Mounting type	Rear mounting Pg9 With flat nut
Assembly note	With flat nut

Product properties

Product type	Circular connectors (device side)
Number of positions	12
Shielded	yes
Coding	A
Thread type	M12
Insulation characteristics	
Overvoltage category	II

Dimensions

Length of the solder pin	6 mm
	6 mm

3

Material specifications

Degree of pollution

Flammability rating according to UL 94	V0
Seal material	FKM
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Rated surge voltage	0.8 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U _N	30 V
Nominal current I _N	1.5 A



1436783

https://www.phoenixcontact.com/us/products/1436783

Connection data

Conductor connection

Connection method	Solder pins
Contact connection type	Pin
Tightening torque	2 Nm 3 Nm (Installation-side)

Mechanical properties

Mechanical data

	Insertion/withdrawal cycles	> 100

Connector

Connection 1

Head design	Pin
Head cable outlet	straight
Head thread type	M12
Head locking type	SPEEDCON
Coding	A

Cable/line

Ambient temperature (operation)	-40 °C 85 °C (cable, fixed installation)
	-25 °C 85 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67 (When plugged in)
	IP65 (When plugged in)
	IP65/IP67
Ambient temperature (operation) (male connector/female connector)	-25 °C 85 °C (Plug / socket)
	-40 °C 85 °C (without mechanical actuation)
Ambient temperature (operation) (Cable, flexible installation)	-25 °C 85 °C (Cable, flexible installation)
Ambient temperature (operation) (Cable, fixed installation)	-40 °C 85 °C (cable, fixed installation)

Standards and regulations

Standard designation	M12 circular connector
Standards/specifications	according to IEC 61076-2-101




1436783

https://www.phoenixcontact.com/us/products/1436783

Drawings

Schematic diagram



Pin assignment M12 male connector, 12-pos., male side view



1436783

https://www.phoenixcontact.com/us/products/1436783

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1436783

<i>71</i>	UL Recognized Approval ID: E118976-20100522				
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
		30 V	1.5 A	26	-

c 911 us	CULus Recognized Approval ID: E221474-20140616				
		Nominal voltage U_N	Nominal current I _N	Cross section AWG	Cross section mm ²
		30 V	1.5 A	-	-



1436783

https://www.phoenixcontact.com/us/products/1436783

Classifications

_	\sim		۷.۷	0
_	ا د ا	_ <i>F</i>	٠.٢	7.7

	ECLASS-13.0	27440110
Ε٦	ГІМ	
	ETIM 9.0	EC003568
IU	NSPSC	
	UNSPSC 21.0	39121400



1436783

https://www.phoenixcontact.com/us/products/1436783

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	8ec6621b-4363-4145-bc2e-3036fc0c99db

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com