

0830773

https://www.phoenixcontact.com/us/products/0830773

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Equipment marking, Aluminum label, aluminum color, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, mounting type: screw, rivet, Number of individual labels: 1, text field height: 15 mm, text field width: 50 mm



Product description

Note:

Due to the current challenges of the global procurement market, Phoenix Contact has unfortunately been forced to accept an aluminum alloy material quality that may cause the appearance to deviate from the homogenous surface quality that was previously expected. This has no impact on the quality of the aluminum labels themselves or the durability of the printing. The effect is purely visual.

Your advantages

- The markers can be marked quickly, easily, and cost-effectively with the BLUEMARK printing systems
- · Aluminum equipment marking for screwing or riveting
- · Identification made from metal, high strength in a lightweight design
- · Increased durability due to the decoratively anodized surface

Commercial data

Item number	0830773
Packing unit	45 pc
Minimum order quantity	45 pc
Sales key	BG18
Product key	BG241B
GTIN	4046356768801
Weight per piece (including packing)	2.14 g
Weight per piece (excluding packing)	2.18 g
Customs tariff number	76169990
Country of origin	DE



0830773

https://www.phoenixcontact.com/us/products/0830773

Technical data

Product properties

Product type	Gerätemarker
Marking	
Number of individual labels	1
Number of individual labels per row	1
Number of bore holes	2
Identification technology	UV LED technology

Mounting

Mounting type	screw. rivet
Woulding type	Solew, fivet

Material specifications

Color	aluminum color
Base element material	Aluminum
Components	free from silicone, halogen, and cadmium

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C 120 °C (> +80 °C slight changes of the material surface possible)
Recommended ambient temperature (storage/transport)	5 °C 25 °C
Recommended humidity (storage/transport)	$50\ \%$ (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years

Dimensions

Width	59.70 mm
Height	14.80 mm
Depth	0.80 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------



0830773

https://www.phoenixcontact.com/us/products/0830773

Classifications

ECLASS

	ECLASS-13.0	27281103
	ECLASS-15.0	27281103
ETIM		
ETIM		
	ETIM 9.0	EC001288
UNSPSC		
	UNSPSC 21.0	39131500



0830773

https://www.phoenixcontact.com/us/products/0830773

Environmental product compliance

EU RoHS

20 1010		
Fulfills EU RoHS substance requirements	Yes, No exemptions	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com