

1221548

https://www.phoenixcontact.com/us/products/1221548

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mobile thermal transfer printer for marking materials in cartridge format incl. accessories in the practical case from the proven L-BOXX system. The printer can print prepunched labels as well as materials in continuous format up to a material width of 24 mm.

### Product description

The THERMOMARK GO SET contains a mobile printer that elevates the digitalization of industrial identification to a new level with its intuitive operation via smart device. Controlled via the MARKING system app, the robust printer creates markings directly on site. Features such as state-of-the-art interfaces, fully guided creation of application-specific identification solutions, and automatic material detection make the process of creating markings particularly easy and error-free. The ability to print die-cut materials as well as continuous media offers professional users a wide variety of applications in industry and trade.

#### Note:

This product is approved for the following countries only and may only be used in these countries.

Andorra, Armenia, Australia, Austria, Belgium, Brazil, Bulgaria, Canada, Chile, China, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Japan, Kazakhstan, Kyrgyzstan, Latvia, Liechtenstein, Lithuania, Luxembourg, Malta, Monaco, Morocco, Netherlands, New Zealand, Norway, Poland, Portugal, Romania, San Marino, Singapore, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey, Ukraine, United Kingdom, USA, Vatican City

#### Scope of supply:

THERMOMARK GO, case, battery, power supply unit incl. 4 adapters, USB cable, MM-EML (20X8)R C1 WH/BK, brief instructions

### Your advantages

- · Maintenance-free operation with proven thermal transfer printer technology
- · Printing of punched and continuous adhesive labels, insert labels, and shrink sleeves
- Operated entirely via digital devices using the MARKING system app
- User-friendly operation with context-based menu navigation of the MARKING system app and Application Wizards for easily creating applicationspecific marking solutions
- The THERMOMARK GO prints materials in cartridge format, which contain the material to be marked and the appropriate ink ribbon
- · Easy material change with the uniform GO SERIES cartridge system
- · Alternative control via the PROJECT complete software
- Everything needed, always available in the field: The case has sufficient space for your printing system, including accessories and for 9 material cartridges
- Ideal protection of your printing system in all everyday situations thanks to resistant materials and a securely closing buckle
- Easy and efficient storage and transportation of your mobile printing system
- · Maximum flexibility for all transport situations with the proven L-BOXX system

### Commercial data

Item number 1221548



1221548

https://www.phoenixcontact.com/us/products/1221548

| Packing unit                         | 1 pc          |
|--------------------------------------|---------------|
| Minimum order quantity               | 1 pc          |
| Sales key                            | BG01          |
| Product key                          | BG1222        |
| GTIN                                 | 4063151309268 |
| Weight per piece (including packing) | 3,411 g       |
| Weight per piece (excluding packing) | 3,411 g       |
| Customs tariff number                | 84433210      |
| Country of origin                    | CN            |



1221548

https://www.phoenixcontact.com/us/products/1221548

### Set consists of

### THERMOMARK GO - Thermal transfer printer

1090747

https://www.phoenixcontact.com/us/products/1090747



Mobile thermal transfer printer for marking materials in cartridge format incl. accessories. The printer can print prepunched labels as well as materials in continuous format up to a material width of 24 mm

### THERMOMARK GO ACCU - Battery

0805009

https://www.phoenixcontact.com/us/products/0805009



Battery for mobile operation of the THERMOMARK GO and THERMOMARK GO.K / THERMOFOX printers.



1221548

https://www.phoenixcontact.com/us/products/1221548

## THERMOMARK GO ADAPTER - Power supply unit

0805010

https://www.phoenixcontact.com/us/products/0805010



Power supply unit incl. 4 adapters for operation of the THERMOMARK GO and THERMOMARK GO.K / THERMOFOX printers.

### MM-EML (20X8)R C1 WH/BK - Label

1116204

https://www.phoenixcontact.com/us/products/1116204



Label, Roll, white/black, unmarked, can be labeled with: THERMOMARK GO, mounting type: adhesive, Number of individual labels: 297, text field height: 8 mm, text field width: 20 mm



1221548

https://www.phoenixcontact.com/us/products/1221548

### THERMOMARK GO CASE - Case

1229456

https://www.phoenixcontact.com/us/products/1229456



Practical and robust case for storing the THERMOMARK GO and THERMOMARK GO.K mobile printers as well as accessories. The case offers space for 9 material cartridges and maximum flexibility for all transport situations thanks to the proven L-BOXX system.



1221548

https://www.phoenixcontact.com/us/products/1221548

## Technical data

### Product properties

| Product type              | Marking system   |
|---------------------------|--|
| Scope of supply           | THERMOMARK GO, case, battery, power supply unit incl. 4 adapters, USB cable, MM-EML (20X8)R C1 WH/BK, brief instructions |
| Marking                   |  |
| Identification technology | Thermal transfer   |
| Device properties         |  |
| Print width               | 22 mm  |
| Print resolution          | 203 dpi  |
| Operating system          | Windows 10, Windows Server 2016, Windows Server 2019, Windows Server 2022  |

### Electrical properties

#### Supply

| Supply voltage range 100 | V AC 240 V AC (50 Hz 60 Hz) |
|--------------------------|-----------------------------|
|--------------------------|-----------------------------|

### Dimensions

| Width  | 135 mm |
|--------|--------|
| Height | 175 mm |
| Length | 70 mm  |

### Environmental and real-life conditions

#### Ambient conditions

| Ambient temperature (operation) | 5 °C 40 °C |
|---------------------------------|------------|



1221548

https://www.phoenixcontact.com/us/products/1221548

## Classifications

### **ECLASS**

|        | ECLASS-13.0 | 19140104 |
|--------|-------------|----------|
|        | ECLASS-15.0 | 19140104 |
| ETIM   |             |          |
|        | TIVI        |          |
|        | ETIM 9.0    | EC001684 |
|        | JORGO       |          |
| UNSPSC |             |          |
|        | UNSPSC 21.0 | 43212100 |



1221548

https://www.phoenixcontact.com/us/products/1221548

## Environmental product compliance

#### EU RoHS

| Yes   |
|---|
| 165   |
| 7(c)-I  |
|   |
| EFUP-10   |
| An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
|   |
| No substance above 0.1 wt%  |
|   |

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com