

1491750

https://www.phoenixcontact.com/ca/products/1491750

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Distributor box, application: Standard, connection method: M12 socket / M12 PUSH-PULL female connector, number of slots: 8, number of positions: 5, coding: A, slot assignment: Double, status display: yes, PNP; master cable connection: M23 plug-in connection (for standard and ONECLICK fast-locking system) 90°, shielding: no

Your advantages

- · Safety in the field, thanks to molded housing and high degree of protection
- Fast, secure installation of connectors with the push-pull fast-locking system in accordance with IEC 61076-2-010
- · Save space: distributor box with double occupancy for two sensors in one slot

Commercial data

Item number	1491750
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	AF3CBB
GTIN	4063151940409
Weight per piece (including packing)	271.7 g
Weight per piece (excluding packing)	271.7 g
Country of origin	DE



1491750

https://www.phoenixcontact.com/ca/products/1491750

Technical data

Notes

Assembly note	NOTE: Observe the permissible bending radii when routing cables, since the degree of protection may be at risk if the bending forces are too high. Reduce mechanical loads upstream of the connector, e.g., by using cable ties.
Note on application	Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories".
Note on application	An O-ring is required when using an M23 screw connector.

Product properties

Product type	Distributor box
Application	Standard
Number of positions	5
Number of slots	8
Coding	A

Electrical properties

Max. operating voltage U _{max}	30 V DC
Nominal voltage U _N	24 V DC
Rated current, total	12 A
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	4 A

Connection data

Conductor connection

Sensor/actuator connection system	M12 socket	
Connection assignment		
Slot/position = Wire color or connection	1 / 4 (A) = 15	
	1 / 2 (B) = 7	
	2 / 4 (A) = 5	
	2 / 2 (B) = 4	
	3 / 4 (A) = 16	
	3 / 2 (B) = 8	
	4 / 4 (A) = 3	
	4 / 2 (B) = 14	
	5 / 4 (A) = 17	
	5 / 2 (B) = 9	
	6 / 4 (A) = 2	
	6 / 2 (B) = 13	
	7 / 4 (A) = 11	
	7 / 2 (B) = 10	



1491750

https://www.phoenixcontact.com/ca/products/1491750

	8 / 4 (A) = 1
	8 / 2 (B) = 18
	1-8 / 1 (+ 24 V) = 19
	1-8 / 3 (0 V) = 6
	1-8 / 5 (PE) = 12
gnaling	
Status display present	yes
imensions	
Dimensional drawing	160 4.5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Width	56 mm
Height	35.2 mm
Length	160 mm
aterial specifications	
Material Housing	РВТ
Flammability rating according to UL 94	VO
Seal material	FKM
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA
Material of contact, master cable side	CU alloy
Material of contact surface, master cable side	gold-plated
able/line	
Connection method	M23 plug-in connection (for standard and ONECLICK fast-

Connection method	M23 plug-in connection (for standard and ONECLICK fast-
	locking system)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C 80 °C





1491750

https://www.phoenixcontact.com/ca/products/1491750

Drawings

Dimensional drawing









https://www.phoenixcontact.com/ca/products/1491750





M12 slot, socket, 5-pos.

Schematic diagram



M23 plug connection pin, 19-pos.



1491750

https://www.phoenixcontact.com/ca/products/1491750

Classifications

ETIM 9.0

ECLASS

	ECLASS-13.0	27440111
	ECLASS-15.0	27440111
ET	ТІМ	

EC003558



1491750

https://www.phoenixcontact.com/ca/products/1491750

Environmental product compliance

EU RoHS

20 1.01.0	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Ltd 8240 Parkhill Drive Milton, Ontario L9T 5V7 1-800-890-2820 cdinfo@phoenixcontact.ca