

1621215

https://www.phoenixcontact.com/us/products/1621215

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, straight, Screw locking mechanism, No. of pos.: 17, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, cable diameter range: 3 mm ... 10.5 mm, this item is expected to be lead-free from Q1 2026 in accordance with RoHS II without exception 6c (Pb < 0.1%), a lead-free alternative is possible on request in advance

### Commercial data

| Item number                          | 1621215                        |
|--------------------------------------|--------------------------------|
| Packing unit                         | 20 pc                          |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Product key                          | ABRAFA                         |
| GTIN                                 | 4046356896375                  |
| Weight per piece (including packing) | 76.42 g                        |
| Weight per piece (excluding packing) | 67.709 g                       |
| Country of origin                    | DE                             |



1621215

https://www.phoenixcontact.com/us/products/1621215

### Technical data

|     | Order information: | Order crimp contacts Ø 1 mm separately |
|-----|--------------------|--|
| Pro | oduct properties   |  |
|     | Product type       | Circular connector (cable-side)        |

#### Connector

#### Insulating body

| <u> </u>               |   |
|------------------------|---|
| Note                   | Order information: Order crimp contacts Ø 1 mm separately |
| Connection method      | Crimp connection  |
| Contact switching type | Pin   |
| Application            | Signal  |
| Number of positions    | 17  |
| Direction of rotation  | Standard  |
| Connection profile     | 17  |

#### Housing

| Note                              | Order contact inserts separately |
|-----------------------------------|----------------------------------|
| Туре                              | Cable connector housing          |
| Thread type                       | M23                              |
| Design                            | straight                         |
| Type of locking                   | Screw locking mechanism          |
| Pg screw connection               | none                             |
| Material (Housing)                | Metal                            |
| Degree of protection (plugged in) | IP65                             |
|                                   | IP67                             |
|                                   | IP68                             |

#### Seal

| External cable diameter | 3 mm 10.5 mm |
|-------------------------|--------------|
| Seal material           | NBR          |



1621215

https://www.phoenixcontact.com/us/products/1621215

## Classifications

#### **ECLASS**

|    | ECLASS-13.0 | 27440116 |
|----|-------------|----------|
|    | ECLASS-15.0 | 27440116 |
| ΕΊ | ГІМ         |          |
|    | ETIM 9.0    | EC002635 |
| U  | NSPSC       |          |
|    | UNSPSC 21.0 | 39121400 |



1621215

https://www.phoenixcontact.com/us/products/1621215

### Environmental product compliance

#### EU RoHS

| Yes   |
|---|
| 6(c)  |
|   |
| EFUP-50   |
| An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
|   |
| Lead(CAS: n/a)  |
| f6735dc6-128c-44d6-91b5-518ef258141d  |
|   |

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com