

0830735

https://www.phoenixcontact.com/us/products/0830735

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Label for rough surfaces, Roll, silver, unmarked, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, Number of individual labels: 300, text field height: 73 mm, text field width: 100 mm

### Your advantages

- The EML-HA ... self-adhesive device markers are suitable for identification of various types of equipment in controller, system, and control cabinet building
- The EML-HA features a special adhesive with a very high bonding strength. This means it can be stuck onto rough, textured, and low-energy surfaces
- · When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- The EML-HA ... materials are UL-listed
- · Marking service: Phoenix Contact can custom-mark all EML-HA ... markers according to your requirements

### Commercial data

| Item number                          | 0830735       |
|--------------------------------------|---------------|
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BG16          |
| Product key                          | BG2411        |
| GTIN                                 | 4046356738781 |
| Weight per piece (including packing) | 565.3 g       |
| Weight per piece (excluding packing) | 532.9 g       |
| Customs tariff number                | 39269097      |
| Country of origin                    | PL            |



0830735

https://www.phoenixcontact.com/us/products/0830735

## Technical data

### Product properties

| Product type                        | Gerätemarker               |
|-------------------------------------|----------------------------|
| Product property                    | highly adhesive            |
| Marking                             |                            |
| Number of individual labels         | 300                        |
| Number of individual labels per row | 1                          |
| Identification technology           | Thermal transfer for rolls |

### **Dimensions**

| Width  | 100.00 mm |
|--------|-----------|
| Height | 73.00 mm  |
| Depth  | 0.11 mm   |

### Material specifications

| RoHS compliant    | yes                            |
|-------------------|--------------------------------|
| Foil strength     | 56 μm                          |
| Adhesive strength | 65 μm                          |
| Color             | silver                         |
| Material          | Polyester                      |
| Components        | free from silicone and halogen |

#### Environmental and real-life conditions

[CAS No. 110-54-3]
Water + Petroleum ether

[CAS No. 64742-82-1]

Test for substances that would hinder coating with paint or varnish

| Result                          | Test passed                                    |
|---------------------------------|--|
| UV resistance                   |  |
| Specification                   | ISO 4892-2:2013-03 (following)                 |
| Result                          | Test passed                                    |
| Test duration                   | 96 h   |
| Procedure                       | Artificial irradiation.                        |
| Wipe resistance of inscriptions |  |
| Specification                   | DIN EN 61010-1 (VDE 0411-1):2011-07            |
|                                 | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropyl<br>[CAS No. 67-63-0]  | Test passed                                    |
| n-Hexane                        | Test passed                                    |

Testing in a condensation changing climate in the presence of sulfur dioxide

| Specification | DIN 50018:2013-05 |
|---------------|-------------------|

Test passed



0830735

https://www.phoenixcontact.com/us/products/0830735

| Result  | Test passed   |
|---|---|
| Climate level                                       | AHT 1.0 S   |
| Cycles  | 2   |
| Salt spray test                                     |   |
| Specification                                       | DIN EN 60068-2-11:2000-02   |
| Result  | Test passed   |
| Test duration                                       | 96 h  |
| Ambient conditions                                  |   |
| Ambient temperature (operation)                     | -40 °C 105 °C   |
| Ambient temperature (assembly)                      | > 5 °C  |
| Recommended storage conditions                      | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |
| Recommended ambient temperature (storage/transport) | 23 °C   |
| Recommended humidity (storage/transport)            | 50 % (Storage in a dry and dark place in the original packaging is recommended)                         |
| Shelf life  | 2 years   |
| tandards and regulations                            |   |
| Wipe resistance                                     | DIN EN 61010-1 (VDE 0411-1)   |
| ounting   |   |
| Mounting type                                       | adhesive  |
|   |   |



0830735

https://www.phoenixcontact.com/us/products/0830735

### **Approvals**

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/0830735



**CSA** 

Approval ID: 70191766



**cULus Recognized** Approval ID: MH48542



0830735

https://www.phoenixcontact.com/us/products/0830735

## Classifications

### **ECLASS**

|       | ECLASS-13.0 | 27281103 |
|-------|-------------|----------|
|       | ECLASS-15.0 | 27281103 |
| =     | TIM         |          |
| _ L I | IIVI        |          |
|       | ETIM 9.0    | EC001288 |
| U     | NSPSC       |          |
|       | UNSPSC 21.0 | 39131500 |



0830735

https://www.phoenixcontact.com/us/products/0830735

## Environmental product compliance

#### EU RoHS

| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|
|   |                    |
|   |                    |
| EU REACH SVHC                           |                    |

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com