

1164355

https://www.phoenixcontact.com/us/products/1164355

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect modular, Type 2, Cable set for infrastructure charging socket, 20 A , 480 V AC, Accessories, Single wires, length: 0.3 m, Plug-in mounting, with slip-on sleeve at one end, only for connection to second-generation infrastructure charging sockets from Phoenix Contact, IEC 62196-2

Product description

Cables with slip-on sleeves on one end for connection to infrastructure charging sockets, for charging electric vehicles (EV) with alternating current (AC), for installation in charging stations for electromobility (EVSE)

Your advantages

- · Protected against overheating with precise temperature measurement
- · Flexible mounting and easy maintenance with plug-in cables
- · Available with your logo on request for consistent branding of your charging station
- · Waterproof and dirtproof due to fully molded contacts
- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- · Uniform, space-saving installation space

Commercial data

Item number	1164355
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	EM01
Product key	XWBFLB
GTIN	4063151176785
Weight per piece (including packing)	54.962 g
Weight per piece (excluding packing)	54.962 g
Customs tariff number	85444290
Country of origin	DE



1164355

https://www.phoenixcontact.com/us/products/1164355

Technical data

Product properties

Product type	Cable set for infrastructure charging socket
Product family	CHARX connect modular
Application	only for connection to second-generation infrastructure charging sockets from Phoenix Contact
Design	with slip-on sleeve at one end
Charging standard	Type 2
Charging mode	Mode 3, Case B

Electrical properties

Charging power and current (AC charging (3-phase))

Type of charging current	AC 3-phase
Charging current	20 A AC (3-phase)
Charging power	16.63 kW (3-phase)
Charging power rating	11 kW (20 A, 3-phase)
Rated voltage	480 V

Pin assignment (Leistungskontakte)

Note on the connection method	Plug-in connection, separable
Number	5 (L1, L2, L3, N, PE)
Rated voltage	480 V AC
Rated current	20 A AC

Pin assignment (Signalkontakte)

Note on the connection method	Plug-in connection, separable
Number	2 (CP, PP)
Rated voltage	30 V AC
Rated current	2 A

Material specifications

Material (Contact surface)	Silver

Cable/line

Cable length	0.3 m
Cable type	Single wires
Cable structure	5 x 2.5 mm² + 2 x 0.5 mm²
Single-core wires for AC	

Single-core wires for AC	
Cable length	0.3 m
Cable structure	5 x 2.5 mm²

Single-core wires for communication



1164355

https://www.phoenixcontact.com/us/products/1164355

Cable length	0.3 m
Cable structure	2 x 0.5 mm ²
Mechanical properties	
Mechanical data	
Insertion/withdrawal cycles	< 3
Environmental and real-life conditions Ambient conditions	
Ambient temperature (operation)	-30 °C 50 °C
Ambient temperature (storage/transport)	-40 °C 80 °C
Altitude	5000 m (above sea level)
Standards and regulations Standards	
Standards/regulations	IEC 62196-2
Standards/regulations	120 02 190-2
Mounting	ILC 02 190-2



1164355

https://www.phoenixcontact.com/us/products/1164355

Classifications

ECLASS

	ECLASS-13.0	27144792
	ECLASS-15.0	27144792
ΕΊ	[−] IM	
	ETIM 9.0	EC002884
U	NSPSC	
	UNSPSC 21.0	39121500



1164355

https://www.phoenixcontact.com/us/products/1164355

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Not applicable, No electrical and electronic equipment (EEE), cannot be used in EEE
EU REACH SVHC	
EU REACH SVIIC	

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com