

1424242

https://www.phoenixcontact.com/us/products/1424242

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 5-position, Pin, straight, M8, B-coding, Wave soldering

Your advantages

- Easy PCB assembly: one-piece connectors for wave soldering
- For high transmission reliability: optional shield connection to the housing and latching on the PCB

Commercial data

Item number	1424242
Packing unit	20 pc
Minimum order quantity	1 pc
Sales key	AB22
Product key	ABQJAA
GTIN	4046356712545
Weight per piece (including packing)	6.365 g
Weight per piece (excluding packing)	6.17 g
Customs tariff number	85366990
Country of origin	DE



1424242

https://www.phoenixcontact.com/us/products/1424242

Technical data

Mounting

Mounting type	Rear mounting (M8 x 1, with flat nut)
Product properties	
Product type	Circular connectors (device side)
Number of positions	5
Shielded	yes
Coding	В
Thread type	M8
Insulation characteristics	
Overvoltage category	II II
Degree of pollution	3

Material specifications

Material Housing	GD-Zn
Material Housing surface	Ni
Material Insulating body	PA 6.6
Material Contact	Cu alloy
Material Contact surface	Au
Flammability rating according to UL 94	НВ

Electrical properties

Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U _N	30 V AC
	30 V DC
Nominal current I _N	3 A

Connection data

Conductor connection

Connection method	Wave soldering
Contact connection type	Pin

Connector

Connection 1

Head design	Pin
Head cable outlet	straight
Head thread type	M8
Coding	В



1424242

https://www.phoenixcontact.com/us/products/1424242

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-25 °C 85 °C
	-25 °C 85 °C

Standards and regulations

Standard designation	M8 circular connector
Standards/specifications	according to IEC 61076-2-104




1424242

https://www.phoenixcontact.com/us/products/1424242

Drawings

Schematic diagram



Pin assignment M8 plug, 5-pos., B-coded, view plug side



1424242

https://www.phoenixcontact.com/us/products/1424242

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1424242

cUL Recognized Approval ID: E221474-20070307					
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
keine					
		30 V	4 A	24	-

<i>7</i> .1	UL Recognized Approval ID: E221474-20	0070307			
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
keine					
		30 V	4 A	24	-



1424242

https://www.phoenixcontact.com/us/products/1424242

Classifications

ECLASS

	ECLASS-13.0	27440110
	ECLASS-15.0	27440110
ET	IM	
	ETIM 9.0	EC003568
LIN	ISPSC	
UI		

UNSPSC 21.0 39121400



1424242

https://www.phoenixcontact.com/us/products/1424242

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	bac2621c-3cb0-4334-97b9-671fbd442fed

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com