

1652680

https://www.phoenixcontact.com/us/products/1652680

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact insert, shell size 3, with 25 signal contacts, type of contact socket, gender changer, fixing with 4-40 UNC thread



Commercial data

| Item number | 1652680 |
|--------------------------------------|---------------|
| Packing unit | 10 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB19 |
| Product key | ABNCAB |
| GTIN | 4017918952808 |
| Weight per piece (including packing) | 18 g |
| Weight per piece (excluding packing) | 17.13 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |



1652680

https://www.phoenixcontact.com/us/products/1652680

Technical data

Product properties

| Product type | Contact insert |
|---------------------|----------------|
| Туре | D-SUB |
| Sensor type | Universal |
| Number of positions | 25 |
| Connection profile | D-SUB |
| Shielded | no |
| Cable outlet | straight |
| | |

Insulation characteristics

| Overvoltage category | III |
|----------------------|-----|
| Degree of pollution | 2 |

Electrical properties

| Rated voltage (III/3) | 125 V |
|-----------------------|--------|
| Rated surge voltage | 1 kV |
| Rated current | 5 A |
| Transmission medium | Copper |
| Power transmission | Power |

Connection data

| Connection method | Coupling |
|-------------------|----------|
|-------------------|----------|

Dimensions

| Width | 17.8 mm |
|--------|----------|
| Height | 53.06 mm |
| Length | 12.55 mm |

Material specifications

| Flammability rating according to UL 94 | V0 |
|----------------------------------------|--------------|
| Housing material | Metal |
| Housing surface material | metal-plated |
| Contact material | Copper alloy |
| Contact surface material | Gold |
| Contact carrier material | Polyester GF |

Mechanical properties

Mechanical data

| Insertion/withdrawal cycles | ≥ 200 |
|-----------------------------|-------|

Environmental and real-life conditions



1652680

https://www.phoenixcontact.com/us/products/1652680

Ambient conditions

| Degree of protection | IP20 |
|---------------------------------|---------------|
| Ambient temperature (operation) | -55 °C 125 °C |

Mounting

| Mounting type Threads |
|-----------------------|
|-----------------------|



1652680

https://www.phoenixcontact.com/us/products/1652680

Classifications

ECLASS

| | ECLASS-13.0 | 27440302 |
|------|-------------|----------|
| | ECLASS-15.0 | 27440323 |
| | -1A 4 | |
| ETIM | | |
| | ETIM 9.0 | EC001132 |
| 1U | NSPSC | |
| | | |
| | UNSPSC 21.0 | 39121400 |



1652680

https://www.phoenixcontact.com/us/products/1652680

Environmental product compliance

EU RoHS

| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|------------------------------------------|
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com