

2721507

https://www.phoenixcontact.com/us/products/2721507

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Network configuration software, copy license, enables the installation and parallel use of the CMD software on multiple workstations. It is a workstation license. A workstation full license is also required.

Product description

A bus system for open, flexible control architectures must provide the user with a concept for universal and, above all, manufacturer-independent operation and diagnostics of a system, in order to provide the required manufacturer-neutrality. The configuration, startup, and diagnostics software CMD (Configuration Monitoring Diagnostics) was developed for INTERBUS. The key features of this software are the independence from the control system used and the flexibility with regard to program expansions, new functions, and utility programs. The DRIVECOM user group, for example, offers utility programs for parameterizing drives according to the DRIVECOM profile.

In order to meet the requirements of users, we continue to apply our INTERBUS expertise to this software.

CMD for all phases:

CMD is a tool that can be used throughout the entire lifecycle of a plant, from planning and configuration, through system startup and operation monitoring, and beyond to diagnostics in the event of maintenance. For the user this eliminates the costs and effort of learning to use several software tools.

The CMD software allows the user to determine the configuration of the INTERBUS system during the configuration phase. The I/O points can be assigned logical addresses or variables, through which the control program will later access the distributed I/Os.

During startup, a function test can be carried out on subsystems using an integrated monitor function.

The diagnostic functions continuously provide detailed information about the bus status, possible error causes, and suggestions on how to remedy them.

CMD for globally established operating systems:

CMD can be run under Windows operating systems for standard PC systems (Windows® NT 4.0 SP6, Windows® 2000, Windows® XP). The familiar interface makes it easy to get started with the software and thereby operate the entire INTERBUS system easily and safely.

The CMD G4 software is not released for Windows 7 operating systems and above. However, the follow-up software Config+ also supports current and future operating systems.

Commercial data

Item number	2721507
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	11
Product key	DRDBAY
GTIN	4017918271367
Weight per piece (including packing)	24.66 g
Weight per piece (excluding packing)	4.5 g
Country of origin	DE



CMD is also available in English, French, Spanish, Portuguese

2721507

https://www.phoenixcontact.com/us/products/2721507

Technical data

Order information:

			•	
ľ	N١	റ	T	20

Product properties	
Product type	Configuration and diagnostics
Basic functions	Executing important commands (start/stop/)
	Reading in the installed bus structure
	Detecting/representing error states (plain text from knowledge database)
	Saving diagnostics data in flash memory or parameterizing memory of the controller board
	Diagnostics of INTERBUS FO paths (transmission quality)
	Configuration comparison of Ethernet topologies (parameterized with real topology)
	Reading out the Controller Diagnose Archive

(Brazilian).

System properties

Intended use for the software	Configuration
	Diagnostics
	Data acquisition
	Communication
	Startup
	Maintenance
	DIN EN 61131-3 compliant
	Security
License information	
Type of license	Copying license
Functionality	

Basic functions	Executing important commands (start/stop/)
	Reading in the installed bus structure
	Detecting/representing error states (plain text from knowledge database)
	Saving diagnostics data in flash memory or parameterizing memory of the controller board
	Diagnostics of INTERBUS FO paths (transmission quality)
	Configuration comparison of Ethernet topologies (parameterized with real topology)
	Reading out the Controller Diagnose Archive
Integrated function	Diagnostics
	Evaluation



2721507

https://www.phoenixcontact.com/us/products/2721507

	Data acquisition
	Startup
	Communication
	Configuration
	Maintenance
Associated hardware	INTERBUS controller boards
Supported controllers	INTERBUS Generation 4 controller board
Number of I/O nodes	not relevant
System requirements	
Operating system	Windows® NT 4.0 SP6
	Windows® 2000
	Windows® XP
Note about the operating system	Does not support Window® 7 and above operating systems
Processor	Min. 80486/ 33 MHz
Hard disk memory	62 Mbyte
RAM	> 10 Mbyte
Interfaces	Free serial interface for online connection
Languages supported	German, English
Optical drive	CD-ROM
Screen resolution	SVGA mit min. 800 x 600



2721507

https://www.phoenixcontact.com/us/products/2721507

Classifications

UNSPSC 21.0

ECLASS	
ECLASS-13.0	27242501
ETIM	
ETIM 9.0	EC000809
UNSPSC	

43233600



2721507

https://www.phoenixcontact.com/us/products/2721507

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Not applicable, No electrical and electronic equipment (EEE), cannot be used in EEE
EU REACH SVHC	
	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com