

https://www.phoenixcontact.com/us/products/1411109



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Screw plug, material for screw connection: Brass, nickel-plated, application: Ex, connecting thread: M32 x 1.5, color: silver-colored

Commercial data

Item number	1411109
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	BF68
Product key	AF7DDX
GTIN	4046356922241
Weight per piece (including packing)	73.16 g
Weight per piece (excluding packing)	72.49 g
Customs tariff number	74198090
Country of origin	GB



https://www.phoenixcontact.com/us/products/1411109



Technical data

Notes

Note on Ex protection	This item must only be used with counter nut 1411244 A-INL-
	M32-N-S for the Ex e type of protection.

Product properties

Product type	Plug for cable screw gland
Application	Ex
Manufacturer	CMP
Manufacturer Designation	757 M32 Exd/Exe N.PLTD HEX HD STOP PLUG
Manufacturer product number	757DM45

Ex data

Suited for EX-applications	yes

Dimensions

Dimensional drawing	20.3
Length	24 mm
Length of the connecting thread	15 mm
Length without connecting thread	9 mm
Diameter	32 mm
Connecting thread diameter	32 mm
Wrench size, union nut	36 mm
Hexagon angular dimension	39.6 mm
Thread type connection side	M32 x 1.5
Thread pitch	1.5 mm

Material specifications

Housing surface material	Ni
Material for screw connection	Brass, nickel-plated

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66 (using the corresponding A-SEWP-W flat gasket)
	IP68 (using the corresponding A-SEWP-W flat gasket)
Ambient temperature (operation)	-60 °C 130 °C

Approvals



1411109

https://www.phoenixcontact.com/us/products/1411109

ATEX	Sira 01ATEX1284U
	Sira 02ATEX1003X
	Ex II 2 GD Ex d IIC & Ex e II, Ex IM2 Ex d I, Ex e I
IECEx	IECEx SIR 07.0056X
	Ex d I / Ex e I / Ex d IIC / Ex e II, Ex tD A21 IP6X
andards and regulations	
Standards/specifications	EN 60079-0, -1, -7
IEC Ex	
Standards/specifications	IEC 60079-0, -1, -7
EN Ex	
Standards/specifications	EN 61241-0, -1
IEC Ex	
Standards/specifications	IEC 61241-0, -1
ounting	
Assembly note	Sealed to IP66/IP68 thanks to the use of the A-SEW-32-P-W flat

gasket (item 1411285)


1411109

https://www.phoenixcontact.com/us/products/1411109



Drawings

Dimensional drawing





1411109

https://www.phoenixcontact.com/us/products/1411109

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1411109



CSA

Approval ID: 113642



UL Listed

Approval ID: E214221



ATEX

Approval ID: CML 18ATEX1320X



1411109

https://www.phoenixcontact.com/us/products/1411109

Classifications

ECLASS

	ECLASS-13.0	23111190
	ECLASS-15.0	23111190
ETIM		
	ETIM 9.0	EC000032
	E11W 0.0	20000002
UI	NSPSC	
	UNSPSC 21.0	31261500



https://www.phoenixcontact.com/us/products/1411109



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	ba0ff755-80af-4d47-b571-1daf94c16010

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com