

2891072

<https://www.phoenixcontact.com/us/products/2891072>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Rack-mount managed Ethernet switch meets IEC 61850-3 and IEEE 1613. Provides 24 RJ45 ports at 10/100 Mbps and four gigabit combo ports (10/100/1000 Mbps RJ45 connection; 1000 Mbps fiber optic connection requires 1000 Mbps SFP module)



Product description

Developed according to IEC 61850-3 (Ambient conditions)

Your advantages

- Network structure according to IEC 61850
- IEEE 1613

Commercial data

Item number	2891072
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DN17
Product key	DNN125
GTIN	4046356764360
Weight per piece (including packing)	5,037 g
Weight per piece (excluding packing)	3,601 g
Customs tariff number	85176200
Country of origin	TW

FL SWITCH 4824E-4GC - Industrial Ethernet Switch



2891072

<https://www.phoenixcontact.com/us/products/2891072>

Technical data

Dimensions

Width	442 mm
Height	44 mm
Depth	375 mm

Notes

Note on application

Note on application	Only for industrial use
---------------------	-------------------------

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Mounting

Mounting type	Rack mount, includes brackets
---------------	-------------------------------

Interfaces

Ethernet (RJ45)

Connection method	RJ45
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100 Mbps
Transmission physics	Ethernet in RJ45 twisted pair
Transmission length	100 m
No. of channels	24 (RJ45 ports)

Ethernet (RJ45/FO combo)

Connection method	SFP/RJ45
Note on the connection method	Auto negotiation and autocrossing (RJ45 interface)
Transmission speed	10/100/1000 Mbps
Transmission physics	Ethernet RJ45 (10/100/1000 Mbps) or SFP (1000 Mbps)
No. of channels	4 (Combo ports)

Product properties

Product type	Switch
Product family	Managed Switch 4000
Type	Block design
MTTF	17.2 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%)
	278 Years (SN 29500 standard, temperature 25°C, operating cycle 21%)
	269.5 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day))
Basic functions	Store and forward switch, Extended Ring and IEEE redundancy,

FL SWITCH 4824E-4GC - Industrial Ethernet Switch



2891072

<https://www.phoenixcontact.com/us/products/2891072>

Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts

Switch functions

Basic functions

Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts

Redundancy

ERR (Extended ring redundancy)

Status and diagnostic indicators

LEDs: U_{S1}, U_{S2} (redundant voltage supply), link and activity per port

Security functions

Basic functions

Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts

Electrical properties

Current consumption

359 mA (115 V AC from FL SWITCH 4800E-P5)

Transmission medium

Copper

FO

Supply

Supply voltage

Based on modular power supplies used

Power supply connection

From FL SWITCH 4800E-P...

Inrush current

18.8 A (48 V DC from FL SWITCH 4800E-P1)

20.7 A (115 V AC from FL SWITCH 4800E-P5)

Current consumption

359 mA (115 V AC from FL SWITCH 4800E-P5)

Environmental and real-life conditions

Ambient conditions

Degree of protection

IP20

Ambient temperature (operation)

-40 °C ... 70 °C

Ambient temperature (storage/transport)

-40 °C ... 85 °C

Permissible humidity (operation)

5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport)

5 % ... 95 % (non-condensing)

Air pressure (operation)

57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Air pressure (storage/transport)

57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Standards and regulations

Standard designation

Ambient conditions

Standards/specifications

IEC 61850-3

EMC data

Noise immunity

IEC 61850-3, IEEE 1613, EN 61000-6-2: 2005

FL SWITCH 4824E-4GC - Industrial Ethernet Switch



2891072

<https://www.phoenixcontact.com/us/products/2891072>

Noise emission

Standards/regulations	EN 61000-6-4
-----------------------	--------------

System properties

Functionality

Basic functions	Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts
-----------------	--

Signaling

Status display	LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port
----------------	--


FL SWITCH 4824E-4GC - Industrial Ethernet Switch



2891072

<https://www.phoenixcontact.com/us/products/2891072>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2891072>



UL Listed

Approval ID: E140403



cUL Listed

Approval ID: E140403



KC

Approval ID: MSIP-REI-PCK-2891072

FL SWITCH 4824E-4GC - Industrial Ethernet Switch



2891072

<https://www.phoenixcontact.com/us/products/2891072>

Classifications

ECLASS

ECLASS-13.0	19170401
ECLASS-15.0	19170401

ETIM

ETIM 9.0	EC000734
----------	----------

UNSPSC

UNSPSC 21.0	43222600
-------------	----------

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	15(a), 6(c), 7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-10
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	01bc8e3a-2db8-4dbb-87ac-e7ac142e491b